

Product Specifications / Technical Data



Collection Name: Elevations AcoustX

Effective: October 2, 2017

Composition:	Vinyl – Soundproof Layer
Size (inches / mm):	7.08" x 47.24" (179.8 x 1199.8mm)
Thickness:	5.0mm-(1.0mm G-core Sound Absorbing Layer)
Wear Layer:	20mil (.5mm)
Finish:	G88 Advanced Coating System
Edge:	Square
Sq.Ft. / Piece:	2.32
Sq.Ft. / Carton:	23.25
Pieces / Carton:	10
Cartons / Pallet:	45 (1046.25 sq.ft.)
Pallets / 20' Container:	20 (20,925 sq.ft.)
Weight / Carton:	40lbs
Limited Warranty:	Lifetime Residential 15 Year Commercial
Testing	
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM E662 Smoke Density (Flaming / Non-Flaming)	Meets and exceeds passing requirements <450
ANSI B101.3 Dynamic Coefficient of Friction	Meets and exceeds passing requirements
ASTM D2047 James Machine Coefficient of Friction (Dry/Wet)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 - Impact Sound Insulation Acoustical Testing (IIC)	55 IIC – Over 6" thick concrete slab (no ceiling assembly)
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements
Sustainability	
Recycled Content:	Yes
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes

www.raskinind.com

1-855 3 RASKIN