Product Specifications / Technical Data
Collection Name: Glory

Effective: June 22, 2016

Composition:	Phthalate-Free Virgin Vinyl
Size (inches / mm):	9.25" x 59.25" (234.95 x 1504.95mm)
Gauge:	.157" (4.0mm)
Wear Layer:	20mil (.5mm)
Finish:	G88 Advanced Coating System
Edge:	Micro-Bevel
Sq.Ft. / Piece:	3.805
Sq.Ft. / Carton:	30.46
Pieces / Carton:	8
Cartons / Pallet:	64 (1,949.44 sq.ft.)
Pallets / 53' Truck:	14 (27,292 sq.ft.)
Weight / Carton:	39.81lbs
Weight / Pallet:	2,597.84lbs
Limited Warranty:	Lifetime Residential 20 Year Commercial
Testing	
ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements (1,000 PSI-Modified)
Sustainability	
Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes

www.floornationusa.com

1-855 3 RASKIN