



Product Specifications / Technical Data

Collection Name: Pride Tile

Effective: March 1, 2018

Composition:	Phthalate-Free Virgin Vinyl
Size (inches / mm):	12" x 24" (304.8 x 609.6mm)
Gauge:	1/8" (3.0mm)
Wear Layer:	20mil (.5mm)
Finish:	G88 Advanced Coating System
Edge:	Square
Sq.Ft. / Piece:	2
Sq.Ft. / Carton:	36
Pieces / Carton:	18
Cartons / Pallet:	48 (1728 sq.ft.)
Pallets / 53' Truck:	22 (38,016 sq.ft.)
Weight / Carton:	36.6lbs
Weight / Pallet:	1800lbs
Limited Warranty:	Lifetime Residential 15 Year Commercial

Testing

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements (1,000 PSI-Modified)

Sustainability

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes

www.floornationusa.com

1-855 3 RASKIN