



## Product Specifications / Technical Data

<b>Item #:</b>	<b>USA-300, 301, 302, 303, 304, 305, 306, 307, 308, 309</b>
Composition:	Phthalate-Free Polyvinyl Chloride
Construction:	Floating Click
Size (inches / mm):	9.13" x 60" (231.90mm x 1,524mm)
Total Thickness:	5.0mm
Wear Layer:	.5mm (20mil)
Finish:	G55 Advanced Ceramic Coating
Edges:	Color Infused Bevel
Sq.Ft. / Piece:	3.80
Sq.Ft. / Carton:	30.43
Pieces / Carton:	8
Cartons / Pallet:	48 (1,460.64 sq.ft.)
Pallets / 20' Container:	20 (29,212.80 sq.ft.)
Weight / Pallet (Lbs):	2,594
Limited Warranty:	Lifetime Residential 10 Year Commercial

### TESTING

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 – Impact Sound Insulation Acoustical Testing (IIC)	51 IIC – over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements

### SUSTAINABILITY

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes