



## Product Specifications / Technical Data

<b>Item #:</b>	<b>USA-220, 222, 223, 224, 225, 226, 227, 228, 229</b>
Composition:	Phthalate-Free Polyvinyl Chloride
Construction:	Floating Click
Size (inches / mm):	7.2" x 48" (182.88mm x 1219.20mm)
Total Thickness:	5.0mm
Wear Layer:	.3mm (12mil)
Finish:	G55 Advanced Ceramic Coating
Edges:	Bevel
Sq.Ft. / Piece:	2.40
Sq.Ft. / Carton:	28.82
Pieces / Carton:	12
Cartons / Pallet:	45 (1,296.90 sq.ft.)
Pallets / 20' Container:	18 (23,344.20 sq.ft.)
Weight / Pallet (Lbs):	2,331.95
Limited Warranty:	20 Year Residential 8 Year Commercial

### TESTING

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 – Impact Sound Insulation Acoustical Testing (IIC)	51 IIC – over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements

### SUSTAINABILITY

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes