Product Specifications / Technical Data Collection: Formations Alpine Plank

Effective:A	nril	26	2024
Effective.A	pill	20,	2024

Composition:	Virgin Vinyl – Dry Back – Phthalate Free		
Size (inches / mm):	7" x 48" (177.80 x 1219.20mm)		
Gauge:	0.08" (2.0mm) and 3.0mm		
Wear Layer:	12mil (.3mm) and 20mil (.5mm)		
Finish:	G55 Advanced Ceramic Bead		
Edge:	Square		
Pcs/Ctn:	20 (2.0mm) 15 (3.0mm)		
SqFt/Ctn:	46.67 (2.0mm) 35 (3.0mm)		
Wt/Ctn:	34.4 Lbs		
Ctns/Plt:	55		
Wt/Plt:	1,905.70 Lbs		
SF/Plt:	2,566.85		
Plts/Ctnr:	20		
SF/Ctnr:	51,337		
Limited Warranty:	25 Year Residential 8 Year Commercial		
Country of Origin:	Korea		
	TESTING		
ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements		
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)		
Slip Resistance:	Meets and exceeds passing requirements for ADA and OSHA Guidelines (>.6)		
ASTM F970 - Static Load Limit:	Meets and exceeds passing weight requirement		
SUS ⁻	TAINABILITY		
Recycled Content:	Yes		
FloorScore [®] Certified:	Yes		
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements		
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements		