

# Product Specifications / Technical Data



Composition:	Phthalate-Free Polyvinyl Chloride
Installation Method:	Snap & Click
Size (inches / mm):	8.97" x 59.84" (227.8 x 1519.9mm)
Total Thickness:	5.0mm
Wear Layer:	20mil (.5mm)
Finish:	G55 Max Advanced Ceramic Bead Coating
Edge:	Color Infused Bevel
Sq.Ft. / Piece:	3.72
Sq.Ft. / Carton:	18.65
Pieces / Carton:	5
Cartons / Pallet:	60 (1,119 sq.ft.)
Pallets / 20' Container:	21 (23,499 sq.ft.)
Weight / Pallet:	1,904.4lbs
Limited Warranty:	25 Year Residential 10 Year Commercial

## Testing

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 – Impact Sound Insulation Acoustical Testing (IIC)	54 IIC – over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements

## Sustainability

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes

[www.luminationusa.com](http://www.luminationusa.com)

1-855 3 RASKIN