

14.8438

6.9689

For detailed installation guidelines or to view our technical data sheets, visit info@raskinind.com or call 1-561-997-6658.

DESCRIPTION:

When it comes to ultimate adaptability to numerous flooring types, Raskin G100 holds the market. Breaking all the rules, this revolutionary product saves time with its instant access to light traffic. G100 provides the waterproof benefits of a hard-set adhesive while aggressively retaining PSA-like surface tack.

APPROVED SUBSTRATES & SURFACES

- APA underlayment grade plywood and OSB
- Association grade particleboard
- Concrete and radiant heated subfloors that do not exceed 85°F (30°C)
- Cement backer board
- Existing well-bonded non-cushion-backed vinyl, tile and sheet flooring
- Fully secured cork underlayments
- Gypsum and lightweight concrete (primed with universal primer)
- Terrazzo (properly prepared with all waxes and surface finishes removed)

SUBSTRATE & SURFACE PREPARATION

Follow flooring manufacturer's guidelines for allowable levels of moisture. Substrate must be prepared per ASTM F710 standards.

- Substrate must be dry, smooth, structurally sound and free of any foreign material that might prevent adhesive bond.
- Fill all cracks, holes and low spots with moisture-resistant patching and self-leveling compounds, allow to fully cure and correct high spots before applying adhesive.
- The substrate, adhesive and flooring must be acclimated in an enclosed building with the HVAC operational between 60-95°F (15-35°C), and between 30-65% relative humidity, for at least 72 hours before, during and after the installation.
- When installing over radiant heated subfloors, turn the heat off for 24 hours before, during and after installation. Failure to turn the heat off may result in shortened working time of the adhesive. When turning radiant heat back on, raise it incrementally, not to exceed a change of more than 5 degrees per hour to a maximum of 85°.

Precautionary Notes:

- Concrete must be placed in strict accordance with applicable standards and specifications. An intact moisture vapor retarder must be present below the concrete (see ASTM E1745), must be fully cured (at least 45 days) and without hydrostatic pressure.
- Although Raskin G100 is a high-moisture tolerant adhesive, it does not form a moisture vapor barrier and will not protect flooring from moisture damage.

APPLICATION INSTRUCTIONS

Follow flooring manufacturer's guidelines for layout, design and any special precautions for installation.

1. Spread adhesive using required tools.
2. Install flooring per the instructions below (open and working times dependent upon temperature and humidity).
 - Wait 30-60 min after adhesive is spread to allow it to dry. Adhesive will darken to visually cue installer.
 - Working time is approximately 12 hrs.
3. Roll and cross roll floor with a 75-100 lbs (34-45 kg) roller at the end of the installation to ensure proper transfer of adhesive.

Precautionary Notes:

- Reseal lid when not in use to protect product.



R A S K I N
I N D U S T R I E S

G100

G100 RESILIENT FLOORING ADHESIVE

RH 95% | pH 5-12 | MVER 10 lbs

FIRM-SET MODIFIED TRANSITIONAL PRESSURE SENSITIVE ADHESIVE

- Immediate access for light traffic (PSA) • ColorReady® technology improves install accuracy •
- High-strength, waterproof bond • PSA performance with hard-set resilience • LEED v4 contributing (CDPH v1.2) •

4 GALLON
(15.14 L)

TROWEL RECOMMENDATIONS:

Porous: LVT/LVP, WPC
Estimated Coverage: 150-180 sf/gal



Non-porous: LVT/LVP
Estimated Coverage: 220-260 sf/gal



CLEANING INSTRUCTIONS

While product is still wet: use a damp cloth and water to remove. While product is still soft: use adhesive remover/stripper, denatured alcohol or mineral spirits. Always check compatibility on a piece of scrap flooring.

STORAGE

This product should be stored at temperatures between 50-90°F (15-32°C). While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN. For more information, refer to SDS (safety data sheet) at tayloradhesives.com.

WARRANTY INFORMATION

For complete warranty information, call (561) 997-6658 visit us on the web at raskinind.com or e-mail us at info@raskinind.com.
SHELF LIFE: 2 years

Manufactured for:
Raskin Industries
710 Powerline Road, Suite G
Deerfield Beach, FL 33442



PN 3014_0719