

AXM201

Axle Load Indicators Single Sensor

Designed for all trucks, prime movers and trailers fitted with air bag suspension systems, the new AXM features a bright LED screen ensuring the display is clearly visible to operators outside the truck; day or night.

The gauge can be configured for any combination of rigid truck with dog trailers or prime mover with 20' & 40' trailers; with the master unit displaying each axle group and the GVM.

Wireless Technology

Built-in wireless technology allows the truck mounted AXM to read data from additional units mounted to each trailer (with AXM Remote).

Display at your fingertips!

Easily see how your truck is being loaded in real time. With an Android smartphone* and Airtec's TruckAXM application you can view a list of axle weights in the cab or within Bluetooth range of your vehicle.

For more information contact airteccorporation.com

* Requires a Bluetooth connection and Airtec's TruckAXM software. The software is designed for Android devices running OS 2.2 or higher.



89AXM201-1001

Product Features

- Bluetooth and Wireless Mesh enabled, RS232 / 485 interface
- Simple 2 stage calibration process
- Universal 7~30 VDC power connection
- Super bright LED display for high visibility night or day

Technical Specifications

Construction	High Impact ABS / Polycarbonate
Dimensions	188W x 168H x 76D mm, 0.8 kg
Power Requirements	7~30 VDC
Inlet Connection	1/4" DOT FMVSS 106 push-to-connect fitting
Unit of Measurement	kPa, kilograms or tonnes
Operating Range	0~120 psi, 0~825 kPa
Accuracy ±	± 0.1 psi Full Scale

Optional Accessories



89AXMRC-1001
LCD Display Unit



89AXL-PDA2
Samsung Galaxy S2
Smartphone Pack



89AXL-WP
Printer Kit, MB200i

Android is a trademark of Google Inc.
Bluetooth is a registered trademark of Bluetooth SIG, Inc.