

# AXM202

## Axle Load Indicators Dual Sensor

Designed for all trucks, prime movers and trailers fitted with air bag suspension systems, the new AXM features a bright LED screen ensuring the display is clearly visible to operators outside the truck; day or night.

The gauge can be configured for any combination of rigid truck with dog trailers or prime mover with 20' & 40' trailers; with the master unit displaying each axle group and the GVM.

### Wireless Technology

Built-in wireless technology allows the truck mounted AXM to read data from additional units mounted to each trailer (with AXM Remote).

### Display at your fingertips!

Easily see how your truck is being loaded in real time. With an Android smartphone\* and Airtec's TruckAXM application you can view a list of axle weights in the cab or within Bluetooth range of your vehicle.

For more information contact [airteccorporation.com](http://airteccorporation.com)

\* Requires a Bluetooth connection and Airtec's TruckAXM software. The software is designed for Android devices running OS 2.2 or higher.



89AXM202-1001

### Product Features

- Bluetooth and Wireless Mesh enabled, RS232 / 485 interface
- Simple 2 stage calibration process
- Universal 7~30 VDC power connection
- Super bright LED display for high visibility night or day

### Technical Specifications

Construction	High Impact ABS / Polycarbonate
Dimensions	188W x 168H x 76D mm, 0.8 kg
Power Requirements	7~30 VDC
Inlet Connection	1/4" DOT FMVSS 106 push-to-connect fitting
Unit of Measurement	kPa, kilograms or tonnes
Operating Range	0~120 psi, 0~825 kPa
Accuracy ±	± 0.1 psi Full Scale

### Optional Accessories



89AXMRC-1001  
LCD Display Unit



89AXL-PDA2  
Samsung Galaxy S2  
Smartphone Pack



89AXL-WP  
Printer Kit, MB200i

Android is a trademark of Google Inc.  
Bluetooth is a registered trademark of Bluetooth SIG, Inc.