

### **PRODUCT SPECIFICATION & TECHNICAL DATASHEET**

# **PW54 - Endurance Plus Visor Helmet**

Collection: Head Protection Range: PPE Materials: ABS, Polycarbonate Outer Carton: 20

## **Product information**

Endurance Plus Visor helmet features an unvented ABS shell, 6-point textile suspension harness, wheel ratchet size adjustment (56-63 cm) as well as comfort sweatband and chin strap. Sold with retractable clear visor PW56 included. Spare parts available.

#### **Head Protection**

Portwest's head protection range aims to benefit our customers by combining the most up to date styles and standards in head protection, irrespective of job or location. Innovative, comfortable and lightweight helmets available for multiple uses.

#### PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

#### **Standards**

EN 397 (-30°C/+50°C, MM, LD, 440V a.c.) EN 50365 Class:0 EN 166 (1 FT) ANSI/ISEA Z89.1 TYPE I (CLASS E)



#### **Features**

- Unvented helmet shell for safe use with electrical applications
- Electrical insulation up to 1000Vac or 1500Vdc (EN 50365)
- $\bullet$  6-point textile suspension harness for enhanced wearer comfort and safety
- Size adjustable headband via wheel ratchet system
- Retractable clear visor included
- Chin strap included
- Compatible with PW47 and PS47 clip-on ear muff
- Compatible with PS58 helmet visor holder
- Replacement visor available
- Available in multiple colourways
- Up to 7 years lifetime from manufacturing date (as long as undamaged)



### **PRODUCT SPECIFICATION & TECHNICAL DATASHEET**

# PW54 - Endurance Plus Visor Helmet Commodity Code: 6506101000

#### **Test House**

INSPEC International B.V. (Notified Body No.: NB: 2849) Beechavenue 54 - 62 , Netherlands Cert No: PPE19161696

### **Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
PW54ORR	Orange	57.0	45.0	44.0	0.4840	0.1129	5036108260683	25036108746525