

TECHNICAL INFORMATION

High environmental quality, 100% natural ecological product.
Decorative wall product. Gives a smooth, satiny finish with marbled effects.
Suitable for interior walls only.
Creamy paste, white. Tools can be cleaned with soap and water.
VOC: 0.00 gms/liter. - Ph: approx.9.
Specific weight : 1.500 kg/liter.

APPLICATION

Prior to using the product and for recommended primers, other surfaces & additional information, refer to the **Surface Preparation Guide** and **Tips** at <https://colorare.com/pages/tips>.

Surfaces: Ideal for use on gypsum/drywall or prepared surfaces with the primer BASE1 or BASE2
Mix before application with a hand or electric whisk.
Apply on a sound (no flaking or peeling) dry surface, free from dirt or dust.
Apply with the use of a trowel, in 2 or 3 very thin coats. The last coat must be almost "transparent". The shininess emerges during the "burnishing" of the 2nd and 3rd coats (lightly pressing the trowel at a 30° angle while the coat is drying.)
Appropriate temperatures for application, between 7°C and 27°C (45°F and 80°F)

DRYING TIMES

Between 6 and 12 hours depending on the room's temperature and humidity level.
The desired tone or coverage is obtained only when the product is completely dried.
The slight odor due to the natural ingredients disappears once drying is complete.
Properly ventilate the room.
Respect stipulated drying times; it is imperative to have a fully dry surface before applying the next coat

DILUTION

No dilution is necessary.
However, if the coating is too thick, it can be diluted with a little water

COVERAGE

Approximately 6-8 sq meters per liter* | 60-80 sqft depending on surface conditions.
*1 liter=1.057 quart.

INGREDIENTS

Milk, egg, arabic gum, linseed oil, beeswax, carnauba wax, cellulose, calcium carbonates, mica, food preservative, borates, water



COLOR-RARE CANADA & USA
www.colorare.com

STUCCO PALLADIO

100% Natural Decorative Wall Coating
MADE IN ITALY

Updated June 1, 2023

STORAGE

Keeps for 12 months in a dry environment protected from frost and excessive heat
Between 5°C and 30°C (40°F and 85°F).

TIPS | SUGGESTIONS

- To obtain an even result, apply from start to finish.
- The surface preparation (smooth and porous) and proper application technique (will vary from one individual to another) is essential for satisfactory results.
- Even though the coating renders a smooth satiny finish, **the product is porous and is not recommended for use in showers!**

The STUCCO PALLADIO advantages

- Gives a smooth, satiny finish, with pretty nuances and patterns.
- Easy to apply.
- Numerous decorative possibilities: doors, decorative wall panels, (ex: headboard, moldings, etc.).
- Can be tinted with pigments.
- Breathable surface.
- 100% VOC FREE

WARNING

- KEEP OUT OF REACH OF CHILDREN
- Do not swallow.
- In case of eye contact, flush immediately with plenty of water.
- Protect from freezing
- Use only with adequate ventilation (to ensure uniform drying)
- This product is non-washable (but is wipeable with a moist sponge)

ADDITIONAL QUESTIONS?

Please visit our FAQ page at www.colorare.com or email us at info@colorare.com.