


The Milk Paint Advantage

- **Economical:** High-coverage, cost-effective paint for interior projects.
- **Natural:** 100% VOC-free, 97% natural milk-based powder for a smooth, matte-velvet finish.
- **Self-Priming:** Works on drywall, wood, plaster, painted surfaces and natural coatings.
- **Easy to Use:** Simple mixing and application—perfect for DIY.
- **Elegant Finish:** Creates a sophisticated, velvety look for your walls.



Mixing



Mix powder with water in 1:1 ratio
Let swell 1-2 hrs

250g + 0.25L (¼ qt) water → ~0.5L (½ qt) paint
1kg + 1L (1 qt) water → ~2L (0.5 gal/2 qts) paint
5kg + 5L (5 qts) water → ~10L (2.5 gal/10 qts) paint

Applying

Apply on clean, dry, sound surfaces (no flaking or dust)


Ideal application temperature: **7-27°C (45-80°F)**.

Mix product thoroughly before and during application

Apply with paint brush or roller in up and down movements

For high traffic areas, a **water-based varnish/topcoat** is recommended.

Milk paint is NOT suitable for wet areas or exterior applications.



WWW.TERRACHROM.COM

Drying time: 5-8 hours
Storage: 12 months
unopened, 1-2 weeks diluted



Refer to the Technical Sheet for
Further Details!