

SOFADHER

Non-granular powder undercoat

SOFADHER is a product of adhesion and a porosity regulator that is used on inappropriate media before the application of whitewash.

Only for interior use.

It is the perfect primer before a Badisof's application (for the Badisof Plus, use Sofix).

Sofadher is a film paint and does not apply on a support that has had covers.

Fiber cement, chipboard, plasterboard (with pre-sanded joints), acrylic-painted interior surfaces, plaster, cement, stone, as well as if you don't know the substrate.

Powder form

SOFADHER comes in a polypropylene bucket. Available in: 1kg - 2 kg - 4 kg.

Coverage on normally absorbent medium

1kg = about 30 m² (depending on support).

Yield given as an indication, depending on substrate.

Dilution

- Dissolve 1 volume SOFADHER in 2 volumes clean water.
- Mix with an electric mixer, at low speed.
- Leave to stand for 5-10 minutes, then stir again.

Application

- Apply the product with a whitewash brush.
- Stir the product throughout application. Apply a second coat if the substrate is very absorbent.
- Allow to dry for 6 hours before applying BADISOF.

Ingredients

Mineral fillers, calcium carbonate (CL 90), talc, vinyl acetate copolymer, cellulose, yellow ochre.

Tips & warnings

- Powdered product: wear a FFP3 mask. See section 7 of the safety data sheet.
- Store in a dry place for 6 months from the date of manufacture shown on the packaging.
- Once in water, the product must be applied.
- Empty packaging can be returned to the manufacturer's plant or recycled at a recycling center
- Ogres de France or TerraChrom cannot be held responsible for incorrect dilution of the product or use on an unsuitable substrate.