

# SOFIX

## Granular powder undercoat

SOFIX is an adhesion-bridging and primer-regulating product for use prior to applying lime whitewash, for interior and exterior use. To go from an uneven surface to a smooth surface. Available in powder form.

SOFIX comes in a polypropylene bucket. Available in: 2,5 kg - 5 kg.

---

### Fields of application

Indoor and outdoor, on substrates such as: MBF, plasterboard, acrylic, plaster, cement, stone. Or even if you don't know your substrate.

---

### Coverage on normally absorbent medium

10 m<sup>2</sup> / kilo / coat

Yield given as an indication, depending on substrate

---

### Ingredients

Mineral fillers, calcium carbonate (CL 90), talc, vinyl acetate copolymer, cellulose, yellow ochre.

---

### Dilution

Dilution will depend on the quality of your substrate whether it's rough, smooth, etc.

### Instructions for interior use

With the 5 kg bucket

- ✓ Mix 5 kg of SOFIX with 5 liters of clean water. Mix to form a paste and leave to stand for 5 minutes.
- ✓ Add 1.5 liters of water, then mix with an electric agitator.

With the 2.5 kg bucket

- ✓ Mix 2.5 kg of SOFIX in 2.5 liters of clean water. Mix to form a paste and leave to stand for 5 minutes.
- ✓ Add 0.75 liters of water, then mix with an electric agitator.

### Instructions for exterior use

With the 5 kg bucket

- ✓ Mix 5 kg of SOFIX with 4 liters of clean water. Mix to form a paste and leave to stand for 5 minutes.
- ✓ Add 8 liters of water, then mix with an electric agitator.

With the 2.5 kg bucket

- ✓ Mix 2,5 kg of SOFIX in 2 liters of clean water. Mix to form a paste and leave to stand for 5 minutes.
- ✓ Add 4 liters of water, then mix with an electric agitator.

---

### Application

- Apply the product with a whitewash brush or wide spalter in criss-cross layers. Stir the product throughout application to prevent the mineral filler from settling to the bottom of the bucket.
- Allow to dry for 24 hours before applying BADISOF PLUS decorating product.

---

### Tips and warnings

- Powdered product: wear a FFP3 MASK. See section 7 of the safety data sheet.
- Store for 6 months in a dry place, starting the date of manufacture shown on the packaging.
- Once in water, the product must be applied.
- Empty packaging can be returned to the manufacturer's plant, or recycled at a recycling center
- Ogres de France or TerraChrom cannot be held responsible for incorrect dilution of the product or use on an unsuitable substrate.