

Laundromat **Stack & Single Tumble Dryer** Specifications

Models	HTT30	HTT45	HT075
Control Options	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600
Capacity – lb (kg)	30 (13) x 2	45 (20) x 2	75 (34)
Width – in (mm)	31.5 (800)	34.5 (875)	38.5 (980)
Depth – in (mm)	43.6 (1110)	49.5 (1260)	53.0 (1350)
Height – in (mm)	76.3 (1940)	81.3 (2065)	77.3 (1960)
Cylinder Diameter – in (mm)	30.0 (762)	33.0 (838)	37.0 (940)
Cylinder Depth – in (mm)	26.0 (660)	30.0 (762)	36.0 (914)
Cylinder Volume – cu ft (liters)	10.6 (300)	14.8 (420)	22.4 (634)
Reversing Cylinder	Standard	Standard	Standard
Door Opening Size – in (mm)	22.6 (574)	26.9 (683)	26.9 (683)
Heat Input Power - Per Pocket – Btu/hr	73,000 x 2	95,000 x 2	165,000
Gas Connections* – in (mm)	0.5	0.5	0.5
Air Outlet – in (mm)	1 x 8 (200) Oval	1 x 10 (250) Oval	8 (200)
Motor - HP	Fan	2 x 0.5	0.5
	Cylinder	2 x 0.5	0.5
Airflow – cfm (liters/sec)	2 x 400 (380)	2 x 600 (285)	800 (380)
Electrical Specs - amps	(B) 100-120V/50/60/1	16	20
	(X) 200-240V/50/60/1/3	9	12
Shipping Dimensions Approx. – in (mm)	Width	32.5 (830)	35.5 (900)
	Depth	47.0 (1190)	54.0 (1370)
	Height	79.9 (2030)	84.9 (2160)
Net Weight – lb (kg)	580 (265)	690 (315)	715 (324)
Shipping Weight – lb (kg)	615 (280)	735 (335)	760 (345)
Agency Approvals	CSA	CSA	CSA

Laundromat **Stack & Single Tumble Dryer** Specifications

Models	HT030	HT055
Control Options	Galaxy™ Touch/600	Galaxy™ Touch/600
Capacity – lb (kg)	30 (13)	55 (24)
Width – in (mm)	27.9 (710)	34.5 (876)
Depth – in (mm)	45.5 (1155)	53.1 (1350)
Height – in (mm)	63.9 (1625)	66.7 (1700)
Cylinder Diameter – in (mm)	26.5 (673)	33 (838)
Cylinder Depth – in (mm)	31.8 (810)	35.0 (889)
Cylinder Volume – cu ft (liters)	9.6 (270)	17.3 (490)
Reversing Cylinder	Standard	Standard
Door Opening Size – in (mm)	22.7 (577)	26.9 (683)
Heat Input Power - Per Pocket – Btu/hr	73,000	112,000
Gas Connections* – in (mm)	0.5	0.5
Air Outlet – in (mm)	6 (150)	8 (200)
Motor - HP	Fan	0.5
	Cylinder	0.5
Airflow – cfm (liters/sec)	500 (240)	700 (330)
Electrical Specs - amps	(B) 100-120V/50/60/1	10
	(X) 200-240V/50/60/1/3	6
Shipping Dimensions Approx. – in (mm)	Width	30.0 (760)
	Depth	49.0 (1240)
	Height	67.6 (1720)
Net Weight – lb (kg)	335 (152)	438 (199)
Shipping Weight – lb (kg)	368 (167)	478 (217)
Agency Approvals	CSA	CSA

* LP gas available for 75 lb capacity only. Field conversion kits available for other capacities.

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. USA and Canada models are certified by CSA International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.