



## Installation Instructions *for Sentry Scale Control System*

**IMPORTANT:** If this system is installed with new copper/brass lines, DO NOT install the filter for 8 weeks in order to let the lines homogenize. Otherwise, the new lines will render the filter useless.



Scan code to watch installation video or visit  
<https://youtu.be/tTYF7O3bFNM>

### STEP 1: Inspect Package Contents

Verify that you have all the necessary components for installation listed below. DO NOT remove plastic film from the water filter until Step 4.

1 Sentry Scale Control Filter Housing	1 Sentry Scale Control Filter	2 Screws	1 Wrench
---------------------------------------	-------------------------------	----------	----------



### STEP 2: Locate Mounting Position

Find the optimal location to mount the housing to the evaporative cooler. Recommended location is approximately 1 inch below the two screws on the evaporative cooler that hold the pad bracket in place. Before installing, ensure that (1) there are no internal water lines or hose pumps in the way and (2) the hose from the housing reaches the hose nipple on the evaporative cooler.



### STEP 3: Mount Water Filter Housing to Evaporative Cooler

Once the optimal position has been located, mount the housing to the evaporative cooler. Place the 2 screws provided through the mounting bracket and, using a drill, attach the housing to the side of the evaporative cooler. Once securely mounted, attach the hose from the housing to the hose nipple on the evaporative cooler and twist firmly into place.



### STEP 4: Install Water Filter\*

Twist off the housing from the lid. Ensuring the filter label is facing the same direction as the housing label, remove the plastic film from the water filter. Keeping the filter in the correct orientation, place it into the housing. Confirm the O-ring is correctly in place to prevent leaks. Thread the housing back onto the mounted lid and securely tighten with the wrench provided.

*For correct filter placement, labels on filter and housing must have same orientation.*



*\*REMEMBER: If this system is installed with new copper/brass lines, DO NOT install the filter for 8 weeks in order to let the lines homogenize.*

### STEP 5: Attach Garden Hose & Turn On Water

Attach garden hose to the hose bib on the housing and twist firmly into place. Turn on water supply and ensure water flows down the pads.



**IMPORTANT:** Replace filter every 12 months or at the beginning of the season to ensure optimal functioning.

**Questions or concerns?** Email us 24/7 at [CleanWater@SentryH2O.com](mailto:CleanWater@SentryH2O.com) or give us a call at 1-833-377-3817 Mon-Fri from 8am-4pm AZ Time.