



**CHALKED
DECORATIVE GLAZE**

DESCRIPTION AND USES

Rust-Oleum® Chalked Decorative Glaze is designed to add a custom antique finish to any surface that has been painted with Rust-Oleum Chalked Paint. This semi-transparent Chalked Decorative Glaze is great for cabinetry, furniture, accessories and more. Decorative Glaze is ideal for Chalked painted surfaces such as wood, laminate, melamine or metal surfaces. **For interior use only.**

PRODUCTS

SKU (236 mL)	Description
310423	Java Brown
310424	Smokey Black

PAINTING CONDITIONS

Use in a well ventilated area when temperature is between 10°C and 35°C and humidity is below 70% to ensure proper drying.

PRODUCT APPLICATION

READ ALL DIRECTION BEFORE BEGINNING PROJECT.

SURFACE PREPARATION

IMPORTANT: Chalked Decorative Glaze must be applied over a clean, fully cured surface that has been painted with Rust-Oleum Chalked Paint. (Chalked Paint surface is fully cured in 3-4 days.) For a high-end finish look, a cloth such as cheesecloth or a lint-free rag should be used to remove portions of the Chalked Decorative Glaze. Make sure to test the glaze in a small inconspicuous area first before beginning project.

PRODUCT APPLICATION (cont.)

APPLICATION

Stir thoroughly to ensure any settled pigment is re-dispersed. Do not shake the can. Thinning is not required. Using a 50mm synthetic brush or 50mm foam brush, coat the surface with the Chalked Decorative Glaze. Be certain to apply the Decorative Glaze in all corners, crevices and raised panel sections. Using cheesecloth, wipe the surface (using varying pressure) to remove the Chalked Decorative Glaze to the desired look. If not satisfied with the appearance of the Decorative Glaze, while wet, lightly wipe the surface with a clean damp cloth and repeat the glazing process.

DRY & RECOAT

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Allow the base coat to dry for 4-8 hours. Allow the Chalked Decorative Glaze to dry for 8 hours before applying the Chalked Clear Topcoat for added durability.

CLEAN-UP

Clean brush and other and application tools immediately with soap and water.

COVERAGE

Up to 4 m².

TECHNICAL DATA

CHALKED DECORATIVE GLAZE

PHYSICAL PROPERTIES

		CHALKED DECORATIVE GLAZE
Resin Type		Styrene Acrylic
Pigment Type		None
Solvents		Propylene Glycol and Water
Weight	Per Litre	1.03-1.04 kg
Solids	By Weight	10.2-11.7%
	By Volume	9.1-9.7%
Volatile Organic Compounds		840-854 g/l
Recommended Dry Film Thickness (DFT) Per Coat		Varies depending on depth of colour
Practical Coverage at Recommended DFT		Up to 4 square metres
Dry Times at 21-27°C and 50% Relative Humidity	Allow Base Coat to Dry	4-8 hours
	Allow Decorative Glaze to Dry	8 hours
Shelf Life		3 years
Flash Point		>93°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.