STORM SLGR 1250X Commercial Dehumidifier

Restoration & Moisture & Ventilation

HIGH CAPACITY, COMPACT, LOW TEMPERATURE DEHUMIDIFIERS FOR PROFESSIONAL USES, WATER DAMAGE CONTROL FOR SITE & HIRE INDUSTRY

APPLICATION

Storm SLGR 1250X passed professional testing and its feedback resulted in an amazing outcome Now let us take a close look at the unit's specification and features.

New generation surface scratch **resistance polyethylene shell 25% more** than the previous generation. The all-new rotating shell design is easy to maintain and allows for **easy access to all components.** Telescopic handles and rubber tires allow for units to be stacked together for **both storage and easy transportation.** With the new design and layout of the machine, the volume of the whole machine is **40% smaller than others** on the market. Simplified user controls include **a large LCD display** and **APP control.** The App can control the dehumidifier remotely anytime and anywhere, thus trips to the site to check up can be eliminated.

Storm SLGR 1250X has an extremely driving water removal capacity which makes the machine the authorized one for restoration needs. It features great COP at 2.66 L/kwh , With a huge capacity of 125 PPD at AHAM RH, while the current draw is 8.1 amps. Installation flexibility makes the unit ideal for almost any application. No conventional dehumidifier can perform as efficiently and effectively for water damage restoration as Storm SLGR 1250X. Its wide range of applications include the Hire Industry, Building Industry, Plasterers, Flood & Restoration, Carpet Cleaning, Tradesmen, etc... or anywhere you need to extract moisture at a professional level.

Built in Pump Drain Pipe 19.6 ft Drain Height 19.6 ft



<u>SLGR PRECOOLING</u> <u>CIRCUIT TECHNOLOGY</u>

AUXILIARY FLOW PATH

The auxiliary expansion device receives the refrigerant liquid from the condenser and expands it to lower both the temperature and the pressure of the refrigerant liquid. The sub-cooler receives the cold liquid refrigerant from the auxiliary expansion device and evaporates it into the cold gas cold air. The body refrigerant is returned to the compressor to complete the refrigeration cycle.

EXTERNAL CIRCULATION PRINCIPLE

The humid air reaches the saturated steam state after passing through the microchannel precooler, and the evaporator cools the air to below the dew point, hence increasing the water vapor condensation rate to a liquid, therefore, dehumidifying the air. The dehumidified air is heated by the condenser, then discharged.

SPECIFICATIONS

Power : 115 V/60Hz Current : 8. 1 Amps COP : 2. 66 L/Kwh Size For : Up to 3,000 sq.ft Filter : MERV - 8 Filter Air flow : 300 CFM, 510 CMH Sound Pressure Level : < 60 dBA Refrigerant : R410 Wheel : 2 Wheels Draining : Condensate Pump Functioning Temperature: 33.8 - 110 °F Functioning Humidity Range: 25~80% Capacity: 125 PPD at AHAM Weight: 79.2 lbs Dim (LxWxH): 26.1x15.5x17.6 in Loading quantity : 20": 124 Sets / 40": 280 Sets / 40" HQ: 350 Sets

FEATURES

- cETL certified
- Smart Wi-Fi & APP control
- Easy clean shell can be opened
- to access all components
- Easy to store wires and hoses
- Ducting Options
- Built-in Condensate Pump
- Environmental R410A Refrigerant
- Sturdy handle-Large Diameter
- Wheels

 Microchannel Cold a Heat
 Exchanger

- Rotational Molded Body
- Superior Stacking
- Rotary Compressor
- Ducting Options
- Water-Full Protection
 Automatic Humidistat Control
- Quick Connection to Cable/Hose
- Memory Starting
- MERV-8 Filter
- Low Temperature

STORM SLGR 1250X Commercial Dehumidifier

WHY DEHUMIDIFY?

- To reduce the relative humidity to a safer level which prevents household items, food, medicine, and books get moldy.
- To reduce the relative humidity to a safer level which protects household appliances, computers, cameras, and other instruments from moisture damage.
- To reduce the relative humidity to a safer level which prevents the long-term humidity of the crawl space or basement from generating moisture in the wood of the house structure to cause rot and damage.
- To reduce the relative humidity to a safer level which lets the house stay away from pest infestation.
- To reduce the relative humidity to a safer level which avoids excessive humidity in a space where its easy for mold, mildew, and fungus to thrive.

WHAT CAN WE BENEFIT FROM A HIGH COP DEHUMIDIFIER?

AlorAir High COP Dehunidfiers are affordable solutions to your humidity problems. This investment in indoor air qualiy and inner comfort can be paid back by a few year's energy savings. Customers can save up to \$250 per year in energy cost with dehumidifiers working for their failtes!



And that doesn't include the savings from using themostats instead of air condtioning. Once you are able to maintain a consistent relative hunicity of 50% or less, you will no longer have to keep the thermostat at low, uncomfortable temperatures once used in an effort to control humidity.



This is a very compact dehunidifier that is produced for drying restoration. This unit features a portable design for easy transportation. Its stackable design can not only save the flood restorer more space but also make more numbers of the units that have been transported to the destination for after flood restoration tasks.

As for the tough environment that flood .0disasters might have,Storm SLGR1250X is designed with rugged rotomolded housing which is of high-quality industrial material. It is rugged enough to endure severe collision and corrosion found in water damage restoration and construction.

As the unique design compared with others, we have the humidity sensor in bypass air design which makes the short-cycling go away and creates quick access to the pump and main board.Customers can do it by themselves and service become easy.Preassembly makes the installation process simple, thereby it reduces the overall installation and project cost.

Storm SLGR 1250X is leading the industry by introducing **Rare earth alloy Tube Evaporator.** This new feature will extend the life of the colls. providing protection in corrosive environments and maintain the coill's heat transfer ability over the life of the coil.

E-mail: sales@alorair.com Tel: 1-888-990-7469

