

2.3 Combination Capacity: 3MXM24AVJU9

Cooling [60 Hz, 208 V]

Combination of indoor unit	Type of indoor unit					Capacity of each indoor unit											
						Each capacity (kBtu/h)					Total capacity (kBtu/h)		Total input (W)		Total current (A)		Power factor (%)
	A room	B room	C room	D room	E room	A room	B room	C room	D room	E room	Rating	(min. ~ max.)	Rating	(min. ~ max.)	Rating	(min. ~ max.)	Rating
07	Wall	—	—	—	—	7.00	—	—	—	—	7.00	6.60 ~ 9.30	390	350 ~ 590	1.9	1.7 ~ 2.9	98
09	Wall	—	—	—	—	9.00	—	—	—	—	9.00	6.60 ~ 12.00	600	360 ~ 860	2.9	1.8 ~ 4.2	98
12	Wall	—	—	—	—	12.00	—	—	—	—	12.00	6.70 ~ 16.00	860	360 ~ 1,280	4.2	1.8 ~ 6.3	98
15	Wall	—	—	—	—	15.00	—	—	—	—	15.00	8.00 ~ 20.00	1,070	360 ~ 1,680	5.2	1.8 ~ 8.2	98
18	Wall	—	—	—	—	18.00	—	—	—	—	18.00	8.10 ~ 24.00	1,420	360 ~ 2,190	7.0	1.8 ~ 10.7	98
07 + 07	Wall	Wall	—	—	—	7.00	7.00	—	—	—	14.00	7.80 ~ 18.70	960	330 ~ 1,500	4.7	1.6 ~ 7.4	98
07 + 09	Wall	Wall	—	—	—	7.00	9.00	—	—	—	16.00	7.90 ~ 21.30	1,200	340 ~ 1,830	5.9	1.7 ~ 9.0	98
07 + 12	Wall	Wall	—	—	—	7.00	12.00	—	—	—	19.00	8.00 ~ 25.20	1,560	340 ~ 2,360	7.7	1.7 ~ 11.6	98
07 + 15	Wall	Wall	—	—	—	7.00	15.00	—	—	—	22.00	9.30 ~ 28.80	1,810	340 ~ 2,660	8.9	1.7 ~ 13.0	98
07 + 18	Wall	Wall	—	—	—	6.44	16.56	—	—	—	23.00	11.50 ~ 30.00	1,930	570 ~ 2,790	9.5	2.8 ~ 13.7	98
09 + 09	Wall	Wall	—	—	—	9.00	9.00	—	—	—	18.00	8.00 ~ 24.00	1,410	350 ~ 2,180	6.9	1.7 ~ 10.7	98
09 + 12	Wall	Wall	—	—	—	9.00	12.00	—	—	—	21.00	8.00 ~ 27.60	1,780	350 ~ 2,680	8.7	1.7 ~ 13.1	98
09 + 15	Wall	Wall	—	—	—	8.63	14.38	—	—	—	23.00	11.50 ~ 30.00	1,930	570 ~ 2,800	9.5	2.8 ~ 13.7	98
09 + 18	Wall	Wall	—	—	—	7.67	15.33	—	—	—	23.00	11.50 ~ 30.00	1,930	570 ~ 2,800	9.5	2.8 ~ 13.7	98
12 + 12	Wall	Wall	—	—	—	11.50	11.50	—	—	—	23.00	8.10 ~ 30.00	2,070	350 ~ 3,010	10.2	1.7 ~ 14.8	98
12 + 15	Wall	Wall	—	—	—	10.22	12.78	—	—	—	23.00	11.50 ~ 30.00	1,930	570 ~ 2,800	9.5	2.8 ~ 13.7	98
12 + 18	Wall	Wall	—	—	—	9.20	13.80	—	—	—	23.00	11.60 ~ 30.00	1,930	570 ~ 2,800	9.5	2.8 ~ 13.7	98
15 + 15	Wall	Wall	—	—	—	11.50	11.50	—	—	—	23.00	12.50 ~ 30.00	1,800	560 ~ 2,590	8.8	2.7 ~ 12.7	98
15 + 18	Wall	Wall	—	—	—	10.45	12.55	—	—	—	23.00	12.60 ~ 30.00	1,800	560 ~ 2,590	8.8	2.7 ~ 12.7	98
18 + 18	Wall	Wall	—	—	—	11.50	11.50	—	—	—	23.00	12.70 ~ 30.00	1,800	560 ~ 2,590	8.8	2.7 ~ 12.7	98
07 + 07 + 07	Wall	Wall	Wall	—	—	7.00	7.00	7.00	—	—	21.00	9.10 ~ 27.60	1,680	310 ~ 2,510	8.2	1.5 ~ 12.3	98
07 + 07 + 09	Wall	Wall	Wall	—	—	7.00	7.00	9.00	—	—	23.00	9.20 ~ 30.00	1,910	320 ~ 2,780	9.4	1.6 ~ 13.6	98
07 + 07 + 12	Wall	Wall	Wall	—	—	6.19	6.19	10.62	—	—	23.00	11.40 ~ 30.00	1,910	550 ~ 2,780	9.4	2.7 ~ 13.6	98
07 + 07 + 15	Wall	Wall	Wall	—	—	5.55	5.55	11.90	—	—	23.00	12.40 ~ 30.00	1,780	540 ~ 2,570	8.7	2.6 ~ 12.6	98
07 + 07 + 18	Wall	Wall	Wall	—	—	5.03	5.03	12.94	—	—	23.00	12.50 ~ 30.00	1,780	540 ~ 2,570	8.7	2.6 ~ 12.6	98
07 + 09 + 09	Wall	Wall	Wall	—	—	6.44	8.28	8.28	—	—	23.00	9.30 ~ 30.00	1,910	330 ~ 2,780	9.4	1.6 ~ 13.6	98
07 + 09 + 12	Wall	Wall	Wall	—	—	5.75	7.39	9.86	—	—	23.00	11.40 ~ 30.00	1,920	550 ~ 2,780	9.4	2.7 ~ 13.6	98
07 + 09 + 15	Wall	Wall	Wall	—	—	5.19	6.68	11.13	—	—	23.00	12.50 ~ 30.00	1,780	540 ~ 2,570	8.7	2.6 ~ 12.6	98
07 + 09 + 18	Wall	Wall	Wall	—	—	4.74	6.09	12.18	—	—	23.00	12.60 ~ 30.00	1,780	540 ~ 2,570	8.7	2.6 ~ 12.6	98
07 + 12 + 12	Wall	Wall	Wall	—	—	5.19	8.90	8.90	—	—	23.00	11.50 ~ 30.00	1,920	560 ~ 2,780	9.4	2.7 ~ 13.6	98
07 + 12 + 15	Wall	Wall	Wall	—	—	4.74	8.12	10.15	—	—	23.00	12.50 ~ 30.00	1,780	540 ~ 2,570	8.7	2.6 ~ 12.6	98
07 + 12 + 18	Wall	Wall	Wall	—	—	4.35	7.46	11.19	—	—	23.00	12.60 ~ 30.00	1,780	550 ~ 2,570	8.7	2.7 ~ 12.6	98
07 + 15 + 15	Wall	Wall	Wall	—	—	4.35	9.32	9.32	—	—	23.00	13.50 ~ 30.00	1,710	530 ~ 2,430	8.4	2.6 ~ 11.9	98
09 + 09 + 09	Wall	Wall	Wall	—	—	7.67	7.67	7.67	—	—	23.00	11.50 ~ 30.00	1,920	560 ~ 2,790	9.4	2.7 ~ 13.7	98
09 + 09 + 12	Wall	Wall	Wall	—	—	6.90	6.90	9.20	—	—	23.00	11.50 ~ 30.00	1,920	560 ~ 2,790	9.4	2.7 ~ 13.7	98
09 + 09 + 15	Wall	Wall	Wall	—	—	6.27	6.27	10.45	—	—	23.00	12.50 ~ 30.00	1,790	550 ~ 2,580	8.8	2.7 ~ 12.7	98
09 + 09 + 18	Wall	Wall	Wall	—	—	5.75	5.75	11.50	—	—	23.00	12.60 ~ 30.00	1,790	550 ~ 2,580	8.8	2.7 ~ 12.7	98
09 + 12 + 12	Wall	Wall	Wall	—	—	6.27	8.36	8.36	—	—	23.00	11.50 ~ 30.00	1,920	560 ~ 2,790	9.4	2.7 ~ 13.7	98
09 + 12 + 15	Wall	Wall	Wall	—	—	5.75	7.67	9.58	—	—	23.00	12.60 ~ 30.00	1,790	550 ~ 2,580	8.8	2.7 ~ 12.7	98
09 + 12 + 18	Wall	Wall	Wall	—	—	5.31	7.08	10.62	—	—	23.00	12.60 ~ 30.00	1,790	550 ~ 2,580	8.8	2.7 ~ 12.7	98
09 + 15 + 15	Wall	Wall	Wall	—	—	5.31	8.85	8.85	—	—	23.00	13.60 ~ 30.00	1,660	540 ~ 2,440	8.1	2.6 ~ 12.0	98
12 + 12 + 12	Wall	Wall	Wall	—	—	7.67	7.67	7.67	—	—	23.00	11.60 ~ 30.00	1,920	560 ~ 2,790	9.4	2.7 ~ 13.7	98
12 + 12 + 15	Wall	Wall	Wall	—	—	7.08	7.08	8.85	—	—	23.00	12.60 ~ 30.00	1,790	550 ~ 2,580	8.8	2.7 ~ 12.7	98

- Notes:**
- Cooling capacity is based on 80°FDB (26.7°CDB) / 67°FWB (19.4°CWB) (Indoor temperature), 95°FDB (35°CDB) / 75°FWB (24°CWB) (Outdoor temperature).
Heating capacity is based on 70°FDB (21°CDB) / 60°FWB (15.6°CWB) (Indoor temperature), 47°FDB (8.3°CDB) / 43°FWB (6°CWB) (Outdoor temperature).
 - The total capacity of connected indoor units is up to 39.0 kBtu/h.
 - It is not possible to have only 1 indoor unit connected. Be sure to connect at least 2 indoor units.
 - The above is the value for connecting with the following indoor units.
7.0 kBtu/h class; wall mount type A series
9.0 kBtu/h class; wall mount type A series
12.0 kBtu/h class; wall mount type A series
15.0 kBtu/h class; wall mount type A series
18.0 kBtu/h class; wall mount type A series

3D152670

3D152671

Heating [60 Hz, 208 V]

Combination of indoor unit	Type of indoor unit					Capacity of each indoor unit											
						Each capacity (kBtu/h)					Total capacity (kBtu/h)		Total input (W)		Total current (A)		Power factor (%)
	A room	B room	C room	D room	E room	A room	B room	C room	D room	E room	Rating	(min. ~ max.)	Rating	(min. ~ max.)	Rating	(min. ~ max.)	Rating
07	Wall	—	—	—	—	8.30	—	—	—	—	8.30	4.70 ~ 14.00	710	380 ~ 1,220	3.5	1.9 ~ 6.0	98
09	Wall	—	—	—	—	10.30	—	—	—	—	10.30	4.70 ~ 18.00	880	390 ~ 1,630	4.3	1.9 ~ 8.0	98
12	Wall	—	—	—	—	13.30	—	—	—	—	13.30	4.80 ~ 24.00	1,130	390 ~ 2,240	5.5	1.9 ~ 11.0	98
15	Wall	—	—	—	—	16.30	—	—	—	—	16.30	5.10 ~ 30.00	1,260	370 ~ 2,690	6.2	1.8 ~ 13.2	98
18	Wall	—	—	—	—	19.30	—	—	—	—	19.30	5.20 ~ 36.00	1,510	370 ~ 3,400	7.4	1.8 ~ 16.7	98
07 + 07	Wall	Wall	—	—	—	7.65	7.65	—	—	—	15.30	5.20 ~ 28.00	1,140	330 ~ 2,400	5.6	1.6 ~ 11.8	98
07 + 09	Wall	Wall	—	—	—	7.57	9.73	—	—	—	17.30	5.20 ~ 32.00	1,300	340 ~ 2,840	6.4	1.7 ~ 13.9	98
07 + 12	Wall	Wall	—	—	—	7.44	12.76	—	—	—	20.20	5.20 ~ 36.00	1,550	340 ~ 3,350	7.6	1.7 ~ 16.4	98
07 + 15	Wall	Wall	—	—	—	7.35	15.75	—	—	—	23.10	5.60 ~ 36.00	1,610	320 ~ 3,060	7.9	1.6 ~ 15.0	98
07 + 18	Wall	Wall	—	—	—	6.72	17.28	—	—	—	24.00	9.00 ~ 36.00	1,680	520 ~ 3,040	8.2	2.6 ~ 14.9	98
09 + 09	Wall	Wall	—	—	—	9.65	9.65	—	—	—	19.30	5.30 ~ 36.00	1,470	340 ~ 3,350	7.2	1.7 ~ 16.4	98
09 + 12	Wall	Wall	—	—	—	9.47	12.63	—	—	—	22.10	5.30 ~ 36.00	1,720	340 ~ 3,330	8.4	1.7 ~ 16.3	98
09 + 15	Wall	Wall	—	—	—	9.00	15.00	—	—	—	24.00	8.90 ~ 36.00	1,680	510 ~ 3,040	8.2	2.5 ~ 14.9	98
09 + 18	Wall	Wall	—	—	—	8.00	16.00	—	—	—	24.00	9.00 ~ 36.00	1,630	520 ~ 3,020	8.0	2.6 ~ 14.8	98
12 + 12	Wall	Wall	—	—	—	12.00	12.00	—	—	—	24.00	5.30 ~ 36.00	1,890	350 ~ 3,330	9.3	1.7 ~ 16.3	98
12 + 15	Wall	Wall	—	—	—	10.67	13.33	—	—	—	24.00	9.00 ~ 36.00	1,680	510 ~ 3,030	8.2	2.5 ~ 14.9	98
12 + 18	Wall	Wall	—	—	—	9.60	14.40	—	—	—	24.00	9.10 ~ 36.00	1,630	520 ~ 2,960	8.0	2.6 ~ 14.5	98
15 + 15	Wall	Wall	—	—	—	12.00	12.00	—	—	—	24.00	9.50 ~ 36.00	1,430	470 ~ 2,750	7.0	2.3 ~ 13.5	98
15 + 18	Wall	Wall	—	—	—	10.91	13.09	—	—	—	24.00	9.60 ~ 36.00	1,420	480 ~ 2,680	7.0	2.4 ~ 13.1	98
18 + 18	Wall	Wall	—	—	—	12.00	12.00	—	—	—	24.00	9.70 ~ 36.00	1,420	480 ~ 2,660	7.0	2.4 ~ 13.0	98
07 + 07 + 07	Wall	Wall	Wall	—	—	7.37	7.37	7.37	—	—	22.10	5.60 ~ 36.00	1,480	290 ~ 3,010	7.3	1.4 ~ 14.8	98
07 + 07 + 09	Wall	Wall	Wall	—	—	7.30	7.30	9.39	—	—	24.00	5.70 ~ 36.00	1,650	290 ~ 3,000	8.1	1.4 ~ 14.7	98
07 + 07 + 12	Wall	Wall	Wall	—	—	6.46	6.46	11.08	—	—	24.00	9.00 ~ 36.00	1,600	480 ~ 2,930	7.8	2.4 ~ 14.4	98
07 + 07 + 15	Wall	Wall	Wall	—	—	5.79	5.79	12.41	—	—	24.00	9.60 ~ 36.00	1,390	440 ~ 2,650	6.8	2.2 ~ 13.0	98
07 + 07 + 18	Wall	Wall	Wall	—	—	5.25	5.25	13.50	—	—	24.00	9.70 ~ 36.00	1,390	440 ~ 2,640	6.8	2.2 ~ 13.0	98
07 + 09 + 09	Wall	Wall	Wall	—	—	6.72	8.64	8.64	—	—	24.00	5.70 ~ 36.00	1,590	290 ~ 2,930	7.8	1.4 ~ 14.4	98
07 + 09 + 12	Wall	Wall	Wall	—	—	6.00	7.71	10.29	—	—	24.00	9.10 ~ 36.00	1,590	480 ~ 2,920	7.8	2.4 ~ 14.3	98
07 + 09 + 15	Wall	Wall	Wall	—	—	5.42	6.97	11.61	—	—	24.00	9.60 ~ 36.00	1,380	440 ~ 2,640	6.8	2.2 ~ 13.0	98
07 + 09 + 18	Wall	Wall	Wall	—	—	4.94	6.35	12.71	—	—	24.00	9.70 ~ 36.00	1,380	440 ~ 2,620	6.8	2.2 ~ 12.9	98
07 + 12 + 12	Wall	Wall	Wall	—	—	5.42	9.29	9.29	—	—	24.00	9.20 ~ 36.00	1,580	480 ~ 2,910	7.8	2.4 ~ 14.3	98
07 + 12 + 15	Wall	Wall	Wall	—	—	4.94	8.47	10.59	—	—	24.00	9.70 ~ 36.00	1,380	440 ~ 2,630	6.8	2.2 ~ 12.9	98
07 + 12 + 18	Wall	Wall	Wall	—	—	4.54	7.78	11.68	—	—	24.00	9.80 ~ 36.00	1,330	450 ~ 2,610	6.5	2.2 ~ 12.8	98
07 + 15 + 15	Wall	Wall	Wall	—	—	4.54	9.73	9.73	—	—	24.00	10.20 ~ 36.00	1,190	400 ~ 2,360	5.8	2.0 ~ 11.6	98
09 + 09 + 09	Wall	Wall	Wall	—	—	8.00	8.00	8.00	—	—	24.00	9.10 ~ 36.00	1,590	480 ~ 2,920	7.8	2.4 ~ 14.3	98
09 + 09 + 12	Wall	Wall	Wall	—	—	7.20	7.20	9.60	—	—	24.00	9.20 ~ 36.00	1,580	480 ~ 2,910	7.8	2.4 ~ 14.3	98
09 + 09 + 15	Wall	Wall	Wall	—	—	6.55	6.55	10.91	—	—	24.00	9.70 ~ 36.00	1,380	440 ~ 2,620	6.8	2.2 ~ 12.9	98
09 + 09 + 18	Wall	Wall	Wall	—	—	6.00	6.00	12.00	—	—	24.00	9.80 ~ 36.00	1,330	440 ~ 2,610	6.5	2.2 ~ 12.8	98
09 + 12 + 12	Wall	Wall	Wall	—	—	6.55	8.73	8.73	—	—	24.00	9.20 ~ 36.00	1,570	490 ~ 2,890	7.7	2.4 ~ 14.2	98
09 + 12 + 15	Wall	Wall	Wall	—	—	6.00	8.00	10.00	—	—	24.00	9.80 ~ 36.00	1,330	440 ~ 2,610	6.5	2.2 ~ 12.8	98
09 + 12 + 18	Wall	Wall	Wall	—	—	5.54	7.38	11.08	—	—	24.00	9.80 ~ 36.00	1,330	450 ~ 2,550	6.5	2.2 ~ 12.5	98
09 + 15 + 15	Wall	Wall	Wall	—	—	5.54	9.23	9.23	—	—	24.00	10.30 ~ 36.00	1,150	400 ~ 2,300	5.6	2.0 ~ 11.3	98
12 + 12 + 12	Wall	Wall	Wall	—	—	8.00	8.00	8.00	—	—	24.00	9.30 ~ 36.00	1,530	490 ~ 2,880	7.5	2.4 ~ 14.1	98
12 + 12 + 15	Wall	Wall	Wall	—	—	7.38	7.38	9.23	—	—	24.00	9.80 ~ 36.00	1,330	440 ~ 2,550	6.5	2.2 ~ 12.5	98

- Notes:**
- Cooling capacity is based on 80°FDB (26.7°CDB) / 67°FWB (19.4°CWB) (Indoor temperature), 95°FDB (35°CDB) / 75°FWB (24°CWB) (Outdoor temperature).
Heating capacity is based on 70°FDB (21°CDB) / 60°FWB (15.6°CWB) (Indoor temperature), 47°FDB (8.3°CDB) / 43°FWB (6°CWB) (Outdoor temperature).
 - The total capacity of connected indoor units is up to 39.0 kBtu/h.
 - It is not possible to have only 1 indoor unit connected. Be sure to connect at least 2 indoor units.
 - The above is the value for connecting with the following indoor units.
7.0 kBtu/h class; wall mount type A series
9.0 kBtu/h class; wall mount type A series
12.0 kBtu/h class; wall mount type A series
15.0 kBtu/h class; wall mount type A series
18.0 kBtu/h class; wall mount type A series

3D152677

3D152678

Cooling [60 Hz, 230 V]

Combination of indoor unit	Type of indoor unit					Capacity of each indoor unit											
						Each capacity (kBtu/h)					Total capacity (kBtu/h)		Total input (W)		Total current (A)		Power factor (%)
	A room	B room	C room	D room	E room	A room	B room	C room	D room	E room	Rating	(min. ~ max.)	Rating	(min. ~ max.)	Rating	(min. ~ max.)	Rating
07	Wall	—	—	—	—	7.00	—	—	—	—	7.00	6.60 ~ 9.30	390	350 ~ 590	1.7	1.6 ~ 2.6	98
09	Wall	—	—	—	—	9.00	—	—	—	—	9.00	6.60 ~ 12.00	600	360 ~ 860	2.7	1.6 ~ 3.8	98
12	Wall	—	—	—	—	12.00	—	—	—	—	12.00	6.70 ~ 16.00	860	360 ~ 1,280	3.8	1.6 ~ 5.7	98
15	Wall	—	—	—	—	15.00	—	—	—	—	15.00	8.00 ~ 20.00	1,070	360 ~ 1,680	4.7	1.6 ~ 7.5	98
18	Wall	—	—	—	—	18.00	—	—	—	—	18.00	8.10 ~ 24.00	1,420	360 ~ 2,190	6.3	1.6 ~ 9.7	98
07 + 07	Wall	Wall	—	—	—	7.00	7.00	—	—	—	14.00	7.80 ~ 18.70	960	330 ~ 1,500	4.3	1.5 ~ 6.7	98
07 + 09	Wall	Wall	—	—	—	7.00	9.00	—	—	—	16.00	7.90 ~ 21.30	1,200	340 ~ 1,830	5.3	1.5 ~ 8.1	98
07 + 12	Wall	Wall	—	—	—	7.00	12.00	—	—	—	19.00	8.00 ~ 25.20	1,560	340 ~ 2,360	6.9	1.5 ~ 10.5	98
07 + 15	Wall	Wall	—	—	—	7.00	15.00	—	—	—	22.00	9.30 ~ 28.80	1,810	340 ~ 2,660	8.0	1.5 ~ 11.8	98
07 + 18	Wall	Wall	—	—	—	6.44	16.56	—	—	—	23.00	11.50 ~ 30.00	1,930	570 ~ 2,790	8.6	2.5 ~ 12.4	98
09 + 09	Wall	Wall	—	—	—	9.00	9.00	—	—	—	18.00	8.00 ~ 24.00	1,410	350 ~ 2,180	6.3	1.6 ~ 9.7	98
09 + 12	Wall	Wall	—	—	—	9.00	12.00	—	—	—	21.00	8.00 ~ 27.60	1,780	350 ~ 2,680	7.9	1.6 ~ 11.9	98
09 + 15	Wall	Wall	—	—	—	8.63	14.38	—	—	—	23.00	11.50 ~ 30.00	1,930	570 ~ 2,800	8.6	2.5 ~ 12.4	98
09 + 18	Wall	Wall	—	—	—	7.67	15.33	—	—	—	23.00	11.50 ~ 30.00	1,930	570 ~ 2,800	8.6	2.5 ~ 12.4	98
12 + 12	Wall	Wall	—	—	—	11.50	11.50	—	—	—	23.00	8.10 ~ 30.00	2,070	350 ~ 3,010	9.2	1.6 ~ 13.4	98
12 + 15	Wall	Wall	—	—	—	10.22	12.78	—	—	—	23.00	11.50 ~ 30.00	1,930	570 ~ 2,800	8.6	2.5 ~ 12.4	98
12 + 18	Wall	Wall	—	—	—	9.20	13.80	—	—	—	23.00	11.60 ~ 30.00	1,930	570 ~ 2,800	8.6	2.5 ~ 12.4	98
15 + 15	Wall	Wall	—	—	—	11.50	11.50	—	—	—	23.00	12.50 ~ 30.00	1,800	560 ~ 2,590	8.0	2.5 ~ 11.5	98
15 + 18	Wall	Wall	—	—	—	10.45	12.55	—	—	—	23.00	12.60 ~ 30.00	1,800	560 ~ 2,590	8.0	2.5 ~ 11.5	98
18 + 18	Wall	Wall	—	—	—	11.50	11.50	—	—	—	23.00	12.70 ~ 30.00	1,800	560 ~ 2,590	8.0	2.5 ~ 11.5	98
07 + 07 + 07	Wall	Wall	Wall	—	—	7.00	7.00	7.00	—	—	21.00	9.10 ~ 27.60	1,680	310 ~ 2,510	7.5	1.4 ~ 11.1	98
07 + 07 + 09	Wall	Wall	Wall	—	—	7.00	7.00	9.00	—	—	23.00	9.20 ~ 30.00	1,910	320 ~ 2,780	8.5	1.4 ~ 12.3	98
07 + 07 + 12	Wall	Wall	Wall	—	—	6.19	6.19	10.62	—	—	23.00	11.40 ~ 30.00	1,910	550 ~ 2,780	8.5	2.4 ~ 12.3	98
07 + 07 + 15	Wall	Wall	Wall	—	—	5.55	5.55	11.90	—	—	23.00	12.40 ~ 30.00	1,780	540 ~ 2,570	7.9	2.4 ~ 11.4	98
07 + 07 + 18	Wall	Wall	Wall	—	—	5.03	5.03	12.94	—	—	23.00	12.50 ~ 30.00	1,780	540 ~ 2,570	7.9	2.4 ~ 11.4	98
07 + 09 + 09	Wall	Wall	Wall	—	—	6.44	8.28	8.28	—	—	23.00	9.30 ~ 30.00	1,910	330 ~ 2,780	8.5	1.5 ~ 12.3	98
07 + 09 + 12	Wall	Wall	Wall	—	—	5.75	7.39	9.86	—	—	23.00	11.40 ~ 30.00	1,920	550 ~ 2,780	8.5	2.4 ~ 12.3	98
07 + 09 + 15	Wall	Wall	Wall	—	—	5.19	6.68	11.13	—	—	23.00	12.50 ~ 30.00	1,780	540 ~ 2,570	7.9	2.4 ~ 11.4	98
07 + 09 + 18	Wall	Wall	Wall	—	—	4.74	6.09	12.18	—	—	23.00	12.60 ~ 30.00	1,780	540 ~ 2,570	7.9	2.4 ~ 11.4	98
07 + 12 + 12	Wall	Wall	Wall	—	—	5.19	8.90	8.90	—	—	23.00	11.50 ~ 30.00	1,920	560 ~ 2,780	8.5	2.5 ~ 12.3	98
07 + 12 + 15	Wall	Wall	Wall	—	—	4.74	8.12	10.15	—	—	23.00	12.50 ~ 30.00	1,780	540 ~ 2,570	7.9	2.4 ~ 11.4	98
07 + 12 + 18	Wall	Wall	Wall	—	—	4.35	7.46	11.19	—	—	23.00	12.60 ~ 30.00	1,780	550 ~ 2,570	7.9	2.4 ~ 11.4	98
07 + 15 + 15	Wall	Wall	Wall	—	—	4.35	9.32	9.32	—	—	23.00	13.50 ~ 30.00	1,710	530 ~ 2,430	7.6	2.4 ~ 10.8	98
09 + 09 + 09	Wall	Wall	Wall	—	—	7.67	7.67	7.67	—	—	23.00	11.50 ~ 30.00	1,920	560 ~ 2,790	8.5	2.5 ~ 12.4	98
09 + 09 + 12	Wall	Wall	Wall	—	—	6.90	6.90	9.20	—	—	23.00	11.50 ~ 30.00	1,920	560 ~ 2,790	8.5	2.5 ~ 12.4	98
09 + 09 + 15	Wall	Wall	Wall	—	—	6.27	6.27	10.45	—	—	23.00	12.50 ~ 30.00	1,790	550 ~ 2,580	7.9	2.4 ~ 11.4	98
09 + 09 + 18	Wall	Wall	Wall	—	—	5.75	5.75	11.50	—	—	23.00	12.60 ~ 30.00	1,790	550 ~ 2,580	7.9	2.4 ~ 11.4	98
09 + 12 + 12	Wall	Wall	Wall	—	—	6.27	8.36	8.36	—	—	23.00	11.50 ~ 30.00	1,920	560 ~ 2,790	8.5	2.5 ~ 12.4	98
09 + 12 + 15	Wall	Wall	Wall	—	—	5.75	7.67	9.58	—	—	23.00	12.60 ~ 30.00	1,790	550 ~ 2,580	7.9	2.4 ~ 11.4	98
09 + 12 + 18	Wall	Wall	Wall	—	—	5.31	7.08	10.62	—	—	23.00	12.60 ~ 30.00	1,790	550 ~ 2,580	7.9	2.4 ~ 11.4	98
09 + 15 + 15	Wall	Wall	Wall	—	—	5.31	8.85	8.85	—	—	23.00	13.60 ~ 30.00	1,660	540 ~ 2,440	7.4	2.4 ~ 10.8	98
12 + 12 + 12	Wall	Wall	Wall	—	—	7.67	7.67	7.67	—	—	23.00	11.60 ~ 30.00	1,920	560 ~ 2,790	8.5	2.5 ~ 12.4	98
12 + 12 + 15	Wall	Wall	Wall	—	—	7.08	7.08	8.85	—	—	23.00	12.60 ~ 30.00	1,790	550 ~ 2,580	7.9	2.4 ~ 11.4	98

- Notes:**
- Cooling capacity is based on 80°FDB (26.7°CDB) / 67°FWB (19.4°CWB) (Indoor temperature), 95°FDB (35°CDB) / 75°FWB (24°CWB) (Outdoor temperature).
Heating capacity is based on 70°FDB (21°CDB) / 60°FWB (15.6°CWB) (Indoor temperature), 47°FDB (8.3°CDB) / 43°FWB (6°CWB) (Outdoor temperature).
 - The total capacity of connected indoor units is up to 39.0 kBtu/h.
 - It is not possible to have only 1 indoor unit connected. Be sure to connect at least 2 indoor units.
 - The above is the value for connecting with the following indoor units.
7.0 kBtu/h class; wall mount type A series
9.0 kBtu/h class; wall mount type A series
12.0 kBtu/h class; wall mount type A series
15.0 kBtu/h class; wall mount type A series
18.0 kBtu/h class; wall mount type A series

3D152702

3D152703

Heating [60 Hz, 230 V]

Combination of indoor unit	Type of indoor unit					Capacity of each indoor unit											
						Each capacity (kBtu/h)					Total capacity (kBtu/h)		Total input (W)		Total current (A)		Power factor (%)
	A room	B room	C room	D room	E room	A room	B room	C room	D room	E room	Rating	(min. ~ max.)	Rating	(min. ~ max.)	Rating	(min. ~ max.)	Rating
07	Wall	—	—	—	—	8.30	—	—	—	—	8.30	4.70 ~ 14.00	710	380 ~ 1,220	3.1	1.7 ~ 5.4	98
09	Wall	—	—	—	—	10.30	—	—	—	—	10.30	4.70 ~ 18.00	880	390 ~ 1,630	3.9	1.7 ~ 7.2	98
12	Wall	—	—	—	—	13.30	—	—	—	—	13.30	4.80 ~ 24.00	1,130	390 ~ 2,240	5.0	1.7 ~ 9.9	98
15	Wall	—	—	—	—	16.30	—	—	—	—	16.30	5.10 ~ 30.00	1,260	370 ~ 2,690	5.6	1.6 ~ 11.9	98
18	Wall	—	—	—	—	19.30	—	—	—	—	19.30	5.20 ~ 36.00	1,510	370 ~ 3,400	6.7	1.6 ~ 15.1	98
07 + 07	Wall	Wall	—	—	—	7.65	7.65	—	—	—	15.30	5.20 ~ 28.00	1,140	330 ~ 2,400	5.1	1.5 ~ 10.6	98
07 + 09	Wall	Wall	—	—	—	7.57	9.73	—	—	—	17.30	5.20 ~ 32.00	1,300	340 ~ 2,840	5.8	1.5 ~ 12.6	98
07 + 12	Wall	Wall	—	—	—	7.44	12.76	—	—	—	20.20	5.20 ~ 36.00	1,550	340 ~ 3,350	6.9	1.5 ~ 14.9	98
07 + 15	Wall	Wall	—	—	—	7.35	15.75	—	—	—	23.10	5.60 ~ 36.00	1,610	320 ~ 3,060	7.1	1.4 ~ 13.6	98
07 + 18	Wall	Wall	—	—	—	6.72	17.28	—	—	—	24.00	9.00 ~ 36.00	1,680	520 ~ 3,040	7.5	2.3 ~ 13.5	98
09 + 09	Wall	Wall	—	—	—	9.65	9.65	—	—	—	19.30	5.30 ~ 36.00	1,470	340 ~ 3,350	6.5	1.5 ~ 14.9	98
09 + 12	Wall	Wall	—	—	—	9.47	12.63	—	—	—	22.10	5.30 ~ 36.00	1,720	340 ~ 3,330	7.6	1.5 ~ 14.8	98
09 + 15	Wall	Wall	—	—	—	9.00	15.00	—	—	—	24.00	8.90 ~ 36.00	1,680	510 ~ 3,040	7.5	2.3 ~ 13.5	98
09 + 18	Wall	Wall	—	—	—	8.00	16.00	—	—	—	24.00	9.00 ~ 36.00	1,630	520 ~ 3,020	7.2	2.3 ~ 13.4	98
12 + 12	Wall	Wall	—	—	—	12.00	12.00	—	—	—	24.00	5.30 ~ 36.00	1,890	350 ~ 3,330	8.4	1.6 ~ 14.8	98
12 + 15	Wall	Wall	—	—	—	10.67	13.33	—	—	—	24.00	9.00 ~ 36.00	1,680	510 ~ 3,030	7.5	2.3 ~ 13.4	98
12 + 18	Wall	Wall	—	—	—	9.60	14.40	—	—	—	24.00	9.10 ~ 36.00	1,630	520 ~ 2,960	7.2	2.3 ~ 13.1	98
15 + 15	Wall	Wall	—	—	—	12.00	12.00	—	—	—	24.00	9.50 ~ 36.00	1,430	470 ~ 2,750	6.3	2.1 ~ 12.2	98
15 + 18	Wall	Wall	—	—	—	10.91	13.09	—	—	—	24.00	9.60 ~ 36.00	1,420	480 ~ 2,680	6.3	2.1 ~ 11.9	98
18 + 18	Wall	Wall	—	—	—	12.00	12.00	—	—	—	24.00	9.70 ~ 36.00	1,420	480 ~ 2,660	6.3	2.1 ~ 11.8	98
07 + 07 + 07	Wall	Wall	Wall	—	—	7.37	7.37	7.37	—	—	22.10	5.60 ~ 36.00	1,480	290 ~ 3,010	6.6	1.3 ~ 13.4	98
07 + 07 + 09	Wall	Wall	Wall	—	—	7.30	7.30	9.39	—	—	24.00	5.70 ~ 36.00	1,650	290 ~ 3,000	7.3	1.3 ~ 13.3	98
07 + 07 + 12	Wall	Wall	Wall	—	—	6.46	6.46	11.08	—	—	24.00	9.00 ~ 36.00	1,600	480 ~ 2,930	7.1	2.1 ~ 13.0	98
07 + 07 + 15	Wall	Wall	Wall	—	—	5.79	5.79	12.41	—	—	24.00	9.60 ~ 36.00	1,390	440 ~ 2,650	6.2	2.0 ~ 11.8	98
07 + 07 + 18	Wall	Wall	Wall	—	—	5.25	5.25	13.50	—	—	24.00	9.70 ~ 36.00	1,390	440 ~ 2,640	6.2	2.0 ~ 11.7	98
07 + 09 + 09	Wall	Wall	Wall	—	—	6.72	8.64	8.64	—	—	24.00	5.70 ~ 36.00	1,590	290 ~ 2,930	7.1	1.3 ~ 13.0	98
07 + 09 + 12	Wall	Wall	Wall	—	—	6.00	7.71	10.29	—	—	24.00	9.10 ~ 36.00	1,590	480 ~ 2,920	7.1	2.1 ~ 13.0	98
07 + 09 + 15	Wall	Wall	Wall	—	—	5.42	6.97	11.61	—	—	24.00	9.60 ~ 36.00	1,380	440 ~ 2,640	6.1	2.0 ~ 11.7	98
07 + 09 + 18	Wall	Wall	Wall	—	—	4.94	6.35	12.71	—	—	24.00	9.70 ~ 36.00	1,380	440 ~ 2,620	6.1	2.0 ~ 11.6	98
07 + 12 + 12	Wall	Wall	Wall	—	—	5.42	9.29	9.29	—	—	24.00	9.20 ~ 36.00	1,580	480 ~ 2,910	7.0	2.1 ~ 12.9	98
07 + 12 + 15	Wall	Wall	Wall	—	—	4.94	8.47	10.59	—	—	24.00	9.70 ~ 36.00	1,380	440 ~ 2,630	6.1	2.0 ~ 11.7	98
07 + 12 + 18	Wall	Wall	Wall	—	—	4.54	7.78	11.68	—	—	24.00	9.80 ~ 36.00	1,330	450 ~ 2,610	5.9	2.0 ~ 11.6	98
07 + 15 + 15	Wall	Wall	Wall	—	—	4.54	9.73	9.73	—	—	24.00	10.20 ~ 36.00	1,190	400 ~ 2,360	5.3	1.8 ~ 10.5	98
09 + 09 + 09	Wall	Wall	Wall	—	—	8.00	8.00	8.00	—	—	24.00	9.10 ~ 36.00	1,590	480 ~ 2,920	7.1	2.1 ~ 13.0	98
09 + 09 + 12	Wall	Wall	Wall	—	—	7.20	7.20	9.60	—	—	24.00	9.20 ~ 36.00	1,580	480 ~ 2,910	7.0	2.1 ~ 12.9	98
09 + 09 + 15	Wall	Wall	Wall	—	—	6.55	6.55	10.91	—	—	24.00	9.70 ~ 36.00	1,380	440 ~ 2,620	6.1	2.0 ~ 11.6	98
09 + 09 + 18	Wall	Wall	Wall	—	—	6.00	6.00	12.00	—	—	24.00	9.80 ~ 36.00	1,330	440 ~ 2,610	5.9	2.0 ~ 11.6	98
09 + 12 + 12	Wall	Wall	Wall	—	—	6.55	8.73	8.73	—	—	24.00	9.20 ~ 36.00	1,570	490 ~ 2,890	7.0	2.2 ~ 12.8	98
09 + 12 + 15	Wall	Wall	Wall	—	—	6.00	8.00	10.00	—	—	24.00	9.80 ~ 36.00	1,330	440 ~ 2,610	5.9	2.0 ~ 11.6	98
09 + 12 + 18	Wall	Wall	Wall	—	—	5.54	7.38	11.08	—	—	24.00	9.80 ~ 36.00	1,330	450 ~ 2,550	5.9	2.0 ~ 11.3	98
09 + 15 + 15	Wall	Wall	Wall	—	—	5.54	9.23	9.23	—	—	24.00	10.30 ~ 36.00	1,150	400 ~ 2,300	5.1	1.8 ~ 10.2	98
12 + 12 + 12	Wall	Wall	Wall	—	—	8.00	8.00	8.00	—	—	24.00	9.30 ~ 36.00	1,530	490 ~ 2,880	6.8	2.2 ~ 12.8	98
12 + 12 + 15	Wall	Wall	Wall	—	—	7.38	7.38	9.23	—	—	24.00	9.80 ~ 36.00	1,330	440 ~ 2,550	5.9	2.0 ~ 11.3	98

- Notes:**
- Cooling capacity is based on 80°FDB (26.7°CDB) / 67°FWB (19.4°CWB) (Indoor temperature), 95°FDB (35°CDB) / 75°FWB (24°CWB) (Outdoor temperature).
Heating capacity is based on 70°FDB (21°CDB) / 60°FWB (15.6°CWB) (Indoor temperature), 47°FDB (8.3°CDB) / 43°FWB (6°CWB) (Outdoor temperature).
 - The total capacity of connected indoor units is up to 39.0 kBtu/h.
 - It is not possible to have only 1 indoor unit connected. Be sure to connect at least 2 indoor units.
 - The above is the value for connecting with the following indoor units.
7.0 kBtu/h class; wall mount type A series
9.0 kBtu/h class; wall mount type A series
12.0 kBtu/h class; wall mount type A series
15.0 kBtu/h class; wall mount type A series
18.0 kBtu/h class; wall mount type A series

3D152711

3D152712