


Submittal Page Model: Ventus X 24k-220V IVKH241A - OVKH241A

	Туре		cooling&heating	
hvacmirage.us	Control type		remote	
	Power supply			230V~/60Hz/1P
	Rated cooling capacity		Btu/h	24000
	Rated Heating capacity		Btu/h	24400
	SEER		Btu/W.h	18.0
Job name:	HSPF Rating (Region IV)		Btu/W.h	10.0
	EER			9.5
	COP		W/W	3.0
	- Input Consumption	Cooling	W	2520.0
Location:		Heating	W	2390.0
		Cooling	А	11.2
		Heating	A	10.6
	Maximum Operation Pressure		PSIG	550
	Maximum Fuse Size		А	30
Engineer:	Indoor noise level at cooling	High/Med/Low		50/46/42
	Outdoor noise level	Outdoor noise level		58
Submitted to:	Connecting Pipe	Gas	inches	1/2"
		Liquid	inches	1/4"
Submitted by:	Net dimensions (W x D x H)	Indoor	inch	46.69x13.38x10.23
		Outdoor	inch	33.26x14.96x27.51
	Net weight	Indoor	Ibs	37.5
		Outdoor	Ibs	99.2
	Indoor Unit			
Approval:	Indoor Motor	Motor Model		DC
	Indoor air circulation / Hi			850
Date:	Outdoor Unit			
Bale.	Compressor Brand			SANYO
Construction:	Compressor Model	Operation temperatu	ure	DC
	Outdoor Motor	Motor Brand		Weilling/Broad-Ocean
Unit #:	Outdoor Motor	Motor Model	CFM	DC
	Outdoor air circulation/Hi	Outdoor air circulation/Hi		1760
	Factory Refrigerant R410a cha	Factory Refrigerant R410a charge		50.09
Drawing #:	Line Set Size	Line Set Size		16
	Maximum Allowed Length		ft	65
	Maximum Allowed Height		ft	49
	Operation temperature		°F	61 ~ 88
	Additional refrigerant Charge		Oz/Ft	0.312

cooling&heating



Submittal Page Model: Ventus X 24k-220V IVKH241A - OVKH241A



HVAC Mirage | 6700 Gateway Park Dr, Unit 6 San Diego, CA 92154 | www.hvacmirage.us Mirage products are subject to continuous improvements. Mirage reserves the right to modify product design, specifications and information in this data sheet without notice and without incuring any obligations. PAGE 2-2