

## **Submittal Page**

Model: Ventus X 36k-220V IVKH361A - OVKH361A

## hvacmirage.us

Job name:
Location:
Engineer:
Submitted to:
Submitted by:
Reference:
Approval:
Date:
Construction:
Unit #:
Drawing #:

Туре			cooling&heating	
Control type			remote	
Power supply		230V~/60Hz/1P		
Rated cooling capacity		Btu/h	36000	
Rated Heating capacity		Btu/h	36000	
SEER		Btu/W.h	17.0	
HSPF Rating (Region IV)		Btu/W.h	8.5	
EER		Btu/W.h	9.0	
COP		W/W	2.8	
Input Consumption	Cooling	W	4000.0	
	Heating	W	3760.0	
Rated Current	Cooling	Α	17.7	
	Heating	Α	16.7	
Maximum Operation Pressure		PSIG	550	
Maximum Fuse Size		Α	20	
Indoor noise level at cooling	High/Med/Low		50/46/42	
Outdoor noise level		dB(A)	58	
Connecting Pipe	Gas	inches	5/8"	
	Liquid	inches	1/4"	
Net dimensions (W x D x H)	Indoor	inch	46.69x13.38x10.23	
	Outdoor	inch	35.43x14.17x31.69	
Net weight	Indoor	lbs	38.6	
	Outdoor	lbs	136.7	
Indoor Unit				
Indoor Motor Motor Model			DC	
Indoor air circulation / Hi		CFM	850	
Outdoor Unit				
Compressor Brand			GMCC	
Compressor Model	Operation temperature		DC	
Outdoor Motor	Motor Brand		Weilling/Broad-Ocean	
Outdoor Motor Motor Model			DC	
Outdoor air circulation/Hi		CFM	2110	
Factory Refrigerant R410a charge		OZ	86.42	
Line Set Size		ft	16	
Maximum Allowed Length		ft	98	
Maximum Allowed Height		ft	65	
Operation temperature		°F	61 ~ 88	
Additional refrigerant Charge		Oz/Ft	0.312	
Additional reingerant onlarge	02/11	0.012		



## **Submittal Page**

Model: Ventus X 36k-220V IVKH361A - OVKH361A





