

ACTFLEX 700 PU PRIMER

TECHNICAL DATA SHEET

ACTFLEX 700 PU Primer

15/08/2023

DESCRIPTION

ACTFLEX 700 PU Primer is a quick-drying, moisture-curing synthetic resin solvent primer designed to enhance adhesion and compatibility between ACTECH PROTECTIVE COATINGS' solvent-based Waterproofing Membranes and joint sealants. This single-pack primer can also be effectively used as a bonding agent for most solvent-based polyurethane liquid membranes.

PACKAGING (weight)

- 1L
- 4L
- 17L

ROLLER, BRUSH GRADE OR SPRAY.

PROPERTIES

Appearance:	Translucent Gloss, Viscous Liquid.	Vapor Pressure @ 25oC:	3.8 KPa.
Odour:	Solvent Odour.	Flash Point:	>23 OC.
Solvent Resistant:	Good.	Density @ 25oC:	0.8.0-1.0 G/ML.
Toxicity:	Dry Film Is Not Toxic.	Volatile Content:	<70 %(W/W).
Solubility:	Soluble In Organic Solvent Insoluble In Water.	Touch Dry Time, Minimum:	30 Minutes At 20°C And 50% R.H. 15 Minutes At 30°C And 50% R.H.
Waterproof Time:	3 Hours At 25°C And 50% R.H	Full Cure:	6 Hours At 25°C And 50% R.H.
Coverage:	4m ² To 6m ² /L Depending On Surface.	Application Temperature:	10°C – 26°C.
Usable Period After Opening:	Within Same Day	Shelf Life:	6 Months

Coverage, Drying And Curing Rates Are Given As A Guide Only As They Can Be Affected By Surface Porosity, Humidity, Temperature, Climate Conditions, Ventilation, Application Technique And Dry Film Thickness. Improper Storage May Result In Instability Of Product.

SUITABLE SURFACES

- New and old concrete
- Render
- Masonry
- Timber
- Bricks
- To bond existing waterproofing liquid polyurethane membranes

SURFACE PREPARATION:

Ensure the surface is structurally sound, dry, clean, and free of contaminants. Repair any holes or non-structural cracks. Follow manufacturer specifications for repair systems.

APPLICATION

1. Application Instructions

- Mix the product thoroughly before use.
- Ensure adequate ventilation during application.
- Apply one even coat using a brush, roller, or spray.
- Allow the primer to dry before installing backing rod, sealant, or waterproofing membrane system.
- Do not apply on substrates with surface temperatures below 10°C.
- Perform a sample test application on all substrates to prevent staining.
- Do not use with water-based products.
- Not suitable for exposure to sunlight and must be protected after 48 hours of full cure.

Note: Do not apply onto substrates with surface temperatures under 10°C.

- A sample test application is recommended on all substrates as staining may occur.
- ACTFLEX 700 Primer PU is NOT recommended to be used with water based products.
- ACTFLEX 700 Primer PU is NOT a vapour barrier. Moisture will cause the primer to blister and peel.
- ACTFLEX 700 Primer PU is NOT suitable for exposure to sunlight and must be protected from sunlight after 48 hours of full cure.
- Improper storage may result in instability of product in can.

STORAGE

9 Months when stored locked up in original unopened containers in a cool, dry, well-ventilated place at temperatures between 10°C to 25°C. Storage above this temperature may reduce storage life. Uncured product is combustible so keep away from a sources of heat and ignition and its vapours and DO NOT store in pits, depressions, basements or areas where vapours may be trapped. Keep away from sunlight and moisture - AT 700 PU Primer is sensitive to airborne moisture. It is preferable to use all contents of the container after opening.

Being a moisture cured - Improper storage may result in instability of product in can.

HEALTH AND SAFETY

When handling DO NOT eat, drink or smoke. Always use in a well-ventilated areas and wear Personal Protection Equipment (PPE). Use breathing respirators at all times. Wash hands immediately after use. **DO NOT** allow material to contact humans, exposed food or food utensils. In case of eye contact, rinse with plenty of water: If inhaled, remove to fresh air: or if swallowed, immediately contact Doctor or Poisons Information centre on 131 126 (AUS) and 0800 764 766 (NZ). **IN TRANSPORT EMERGENCY DIAL 000 – POLICE-FIRE BRIGADE.** Keep containers in a well-ventilated place and tightly closed. Local regulations as well as health and safety advice on packaging labels must be observed. For more information, please download a copy of the SDS from www.thewaterproofingshop.com.au KEEP OUT OF REACH OF CHILDREN

SAFETY PRECAUTIONS

When handling DO NOT eat, drink or smoke. ACTFLEX 700 PU Primer is hazardous and may cause skin and eye irritation. Immediately take off all contaminated clothing and thoroughly rinse area that has been in contact with product. Breathing vapours is harmful and may cause asthma like reaction. Use breathing respirators at all times. Organic vapour respirators with particulate pre- filters and powered, air-purifying respirators are NOT suitable. Wear protective gloves, clothing, and safety goggles with side shields and face protection. In case of eye contact, rinse with plenty of water for at least 15 minutes and contact Doctor or Poisons Information Centre. If swallowed do not induce vomiting and immediately contact Doctor or Poisons Information centre on 131 126 (AUS). Avoid release to the environment. Additional information is listed in the Material Safety Data Sheet SDS can be down loaded from www.thewaterproofingshop.com.au .

Data Sheet

This Technical Data Sheet and the Material Safety Data Sheet (SDS) may be revised at any time to comply with relevant changes to the Australian Standards or to include changes to current technology. Always read the current SDS and TDS carefully prior to use, as application and performance data may change from time to time. It is always best to request a copy of the latest technical data from Actech Protective Coatings by calling 02 8021 3517 or emailing admin@actechpc.com.au

CONDITIONS OF USE, PRODUCT DISCLAIMER AND STATEMENT OF RESPONSIBILITY

The information supplied is given in good faith and to the best of our knowledge is true and accurate at the time of printing. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. We reserve the right to update information without prior notice to you to reflect our ongoing research and development program. The customer or the contractor is responsible for checking the suitability of products for their intended use. It is the customers' responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for intended users only. Any advice, recommendation, information, assistance or service provided by Actech Protective Coatings in relation to its products or their use is given in good faith, however is provided without responsibility or liability. To the full extent permitted by law, Actech Protective Coatings Products liability is limited to its discretion, to replace or to refund the purchase price of the quantity of the products supplied. Actech Protective Coatings does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Under no circumstances will the company be liable for loss, consequential or otherwise, arising from the use of the product.