

PAINT FOR PROS®

DARK GREY
M A G N E T P A I N T
BASE COAT



500ML



1L



2,5L



5L



**PAINT
FOR
PROS®**

M A G N E T P A I N T

PAINT WITH A STRONG ATTRACTION

WHAT IS MAGNETPAINT

Paint For Pros MagnetPaint is a primer that contains a special iron powder. By using this paint the treated walls, doors, windows and objects are turned into surfaces which attract magnets. The paint is easy and quick to apply, paintable and easy to wallpaper.

PERFORMANCE

A high-quality and strong paint is obtained by enriching the water-based latex paint with iron powder, which makes it a superior product. It adheres to almost all materials, including plastic and wood. This is what makes this paint a powerful all-rounder!

The magnetic paint is easy to apply. It does not give off any unpleasant odours and is safe to work with, in all areas. MagnetPaint meets the standard (BS EN 71-3: 1995) of being a child-friendly paint.

To ensure an optimal magnetic performance we recommend that you apply three layers of MagnetPaint. After waiting four hours after the first application, the next layer of paint can be applied. After waiting 24 hours the paint can be painted on or wallpapered over.

TIP

The neodymium magnets from Paint For Pros provide even more holding power (up to 20 A4 pages).

MAGNETPAINT SPECIFICATIONS

SHEEN	Mat	
COLOUR	Dark grey	
DENSITY	2.62 gr/cm ³	
FILM THICKNESS	85 µm wet film (1 layer), 250 µm dry film (3 layers)	
THEORETICAL COVERAGE	6m ² / L, one layer	
VISCOSITY	Ready for use. If required, solve with a maximum of 5% clear water	
SPRAYABLE	No	
VOC	U-limit for these products (2004/42/EG, kat. jWb, 2010): 30 g/l. This product contains 0 g/l. VOC.	
APPLICATION	Surface and air temperature should have minimum of 10°C / 50°F.	
DRYING TIME	TOUCH DRY	After 10 minutes @ 20°C and 65 % relative humidity
	RECOATABLE	After 4 hours @ 20°C and 65 % relative humidity
	READY TO USE	After 24 hours @ 20°C and 65 % relative humidity
PACKAGING	500 ML, 1 L, 2,5 L, 5 L and bulk	
SHELF LIFE	Minimum 24 months, if stored in a cool dry area between temperatures of 5-35°C / 40-75°F and keep out of direct sun light, sealed tightly	



- WATERBASED LATEX PRIMER, NO SMELLS, EASY APPLICATION
- AWARDED EN71-3 NORM: SAFE FOR CHILDREN TO PLAY WITH
- HOLDS UP TO 20 SHEETS OF PAPER WITH ONE MAGNET (29 MM NEODYMIUM)
- CAN BE PAINTED OVER IN ANY WAY OR COLOUR