

Nominee 2016



reddot award  
product design



# PAINT FOR PROS<sup>®</sup>

TRANSPARENT  
S K E T C H P A I N T  
DRY ERASE PAINT

AVAILABLE IN:



250ML



500ML



1L



5L



10L



PAINT  
FOR  
PROS<sup>®</sup>

# S K E T C H P A I N T

## TRANSPARENT WHITEBOARDPAINT FOR HEAVYDUTY USE

### WHAT IS SKETCHPAINT

The PAINT FOR PROS SketchPaint is a revolutionary 1-component paint for a super-smooth and high-quality whiteboard. Thanks to its unique composition, SketchPaint makes the surface considerably smoother than all other whiteboard paints after curing.

### PERFORMANCE

SketchPaint is the ideal solution for anyone looking for a high-quality finish as well as best performance. The paint provides a perfect top coat which was specially designed for intensive use in a business environment. This makes the traditional whiteboard a definite thing of the past. The entire wall (or part of it) can be treated with SketchPaint, after which creative plans, projects and overviews can be shared quickly and easily.

The unique composition of SketchPaint means that is a superior product. Unlike other whiteboard paints, SketchPaint can be applied from the tin. The mixing of two components is a thing of the past. The tin can be easily closed after use so that the remainder can be applied at a later stage.

SketchPaint can be utilised after 24 hours of drying and used while most 2-component paints have to dry for 2 to 6 days.

### SKETCHPAINT SPECIFICATIONS

<b>SHEEN</b>	High gloss	
<b>COLOUR</b>	Transparent	
<b>DENSITY</b>	1.07 g/cm <sup>3</sup>	
<b>FILM THICKNESS</b>	70 µm dry film	
<b>THEORETICAL COVERAGE</b>	12 - 14 m <sup>2</sup> /l one coat	
<b>VISCOSITY</b>	Ready for use. If required, solve with a maximum of 3% white spirit	
<b>SPRAYABLE</b>	Yes	
<b>VOC</b>	EU limit value for this product (2004/42/EC, cat. iSB, 2010): 500 g/l. This product contains: 60 gr./LVOC's	
<b>APPLICATION</b>	Surface and air temperature should be between 16-26°C / 60-80°F	
<b>DRYING TIME</b>	<b>TOUCH DRY</b>	After 2 hours @ 20°C and 65 % relative humidity
	<b>RECOATABLE</b>	After 12 hours @ 20°C and 65 % relative humidity
	<b>READY TO USE</b>	After 24 hours @ 20°C and 65 % relative humidity
<b>PACKAGING</b>	250 ML, 500 ML, 1 L, 5 L and 10 L	
<b>SHELF LIFE</b>	Minimum 12 months, if stored in a cool dry area between temperatures of 5-35°C /40-75°F and keep out of direct sun light, sealed tightly	



- SUPER SMOOTH HIGH GLOSS FINISH
- HARD TOP COAT FOR INTENSIVE PROFESSIONAL USE
- 1-COMPONENT PAINT, NO MIXING REQUIRED
- READY TO USE AFTER JUST 24 HOURS
- RE-SEALABLE, FOR USE AT FUTURE PROJECTS

Nominee 2016