



## Fine Marmorino Plaster



### Fine Marmorino Plaster

An Interior crushed marble-based plaster that creates a fine Marmorino style finish.

MADE IN THE USA

#### What is it?

Our Marmorino Plasters represent a set of premium interior finishes, crafted from an acrylic base infused with finely crushed marble and stone. This specialized plaster offers exceptional durability and resilience, creating a luxurious Marmorino-style appearance reminiscent of marble and stone. Its versatility allows for application directly over existing surfaces and level 3 drywall finishes, facilitating seamless integration into a variety of design schemes, ranging from sleek and contemporary to rustic and old-world aesthetics. Whether aiming to emulate the timeless elegance of genuine limestone or achieve a bespoke, textured finish, Fine and Coarse Marmorino Plasters provide an ideal solution for interior enhancements.

#### Benefits

These Marmorino Plasters offer an array of advantages that elevate it to the forefront of interior design. Firstly, their ability to create a professional and timeless marble and stone appearance on diverse surfaces ensures a sophisticated and upscale ambiance in any space. Additionally, this interior acrylic product boasts impressive sandability and patchability, allowing for effortless repairs and maintenance as needed. Another key benefit lies in its eco-friendliness, characterized by ZERO VOC emissions, ensuring a safe and healthy indoor environment. Moreover, the durability and longevity of these stone Marmorino Plasters are unparalleled, making them resistant to the rigors of everyday use and wear. Their inherent moisture resistance further enhances the suitability for high-moisture areas such as bathrooms and kitchens, providing both aesthetic appeal and practical functionality. Whether applied in a smooth, polished manner or with a more textured finish, Fine and Coarse Marmorino Plasters offer unparalleled versatility and enduring beauty for interior spaces.

**CAUTION:** Avoid contact with eyes. May cause irritation. If contact occurs, flush immediately with water and contact physician immediately. If sanding is necessary, use a dust-particulate respiration approved by NIOSH-MSHA.

**WARRANTY:** Since methods and conditions of application and use are beyond our control, our warranties shall not be effective UNLESS the product is applied according to our current printed directions and specifications. The manufacturer shall replace such quantity of products proven to be defective within 1-year following date of manufacturer.

# Fine Marmarino Product Data Sheet

- 1. Packaging** | 42 lbs. (19.05 kg) net weight in 3.5-gallon plastic pail / 48 Pails per pallet.  
12 lbs. (5.44311 kg) net weight in 1-gallon plastic pail / 96 Pails per pallet.
- 2. Storage** | Protect from direct sunlight and keep from freezing. Do not stack more than 3 pails high.  
Shelf life of 12 months. Tightly seal lid when storing.
- 3. Coverage** | Approximately 150-200 square feet per 42 pounds | 30-60 square feet per 12 pounds, depending on surface conditions and thickness of application.
- 4. Mixing** | Thoroughly mix with a drill motor and paddle to achieve an ideal viscosity and color paddle mixer to a homogeneous consistency.
- 5. Drying Time** | Dry to touch in approximately 1-2 hours at 68°F (20°C) and good ventilation.
- 6. Clean-Up** | Wash tools and equipment with water.
- 7. Job and Surface Conditions** | Substrate must be dry, clean, sound, and free from contaminants such as dust, oil, mildew, debris, and efflorescence. Maintain a minimum air temperature of 40°F (4.4°C) during application, and at least 48 hours afterwards. May be applied over new or previously painted surfaces; Glossy surfaces must be roughed to ensure proper bond. Pre-priming over wallpaper recommended.
- MASONRY, CONCRETE, AND PLASTER:** Surfaces should cure for a minimum of 7 days prior to application. **POURED CONCRETE:** Surfaces should cure for a minimum of 28 days prior to finishing.
- 8. Thinning** | Do not thin product.
- 9. Application** | **BASE COAT:** Putty coat over entire surface with standard stainless steel, plastic vinyl, venetian plaster, or drywall trowel. For more uniform color, smooth out lap lines as product sets. To avoid chatter marks, keep trowel flat and do not pull as tight. **TOP COAT:** Repeat steps from base coat and trowel smooth as products sets. If texture is desired, leave pockets of base coat in random areas then trowel smooth. May sand with 325 grit or higher for desired finish. **NOTE:** Higher grit increases "burnish".

## Submittal Approval

Job Name:

Contractor:

Date: