Vella – Marmorino Finishes (Fine & Coarse)

Safety Data Sheet*

Date of issue: 11/25/2015 Revision date: 11/25/2015 Supersedes:

Version: 1.0

ECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier

Product form	:	Mixture
Product name	:	Marmorino Plaster

Quick Identifier Common Name (on label / list)	Packaging	Product Code
Marmorino Finishes (Fine & Coarse)	3.5 gal pail	70002, 70006, 70010
Marmorino Finishes (Fine & Coarse)	1 gal pail	70003, 70007, 70011
Marmorino Finishes (Fine & Coarse)	1 quart pail	70004, 70008, 70012

1.2. Relevant identified uses of the substance or mixture and uses advised against

÷

Use of the substance/mixture Drywall finishing compound : 1.3. Details of the supplier of the safety data sheet SBP Phone number: 1-714-279-1042 1-714-279-1043 145 West Meats Avenue Fax number: Orange, CA, USA 92865 www.specializedbuildingproducts.com Website:

1.4. Emergency telephone number

Emergency number

Chemtrec: 1-800-424-9300

SECTION 2: Hazards identification 2.1. Classification of the substance Classification (GHS-US) Carc. 1A H350 STOT RE 2 H373 Aquatic Acute 3 H402

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling Hazard pictograms (GHS-US)



Signal word (GHS-US)	:	GHS08 Danger
Hazard statements (GHS-US)	:	H350 - May cause cancer (Inhalation)
		H373 - May cause damage to organs (lungs/respiratory system) through prolonged or repeated exposure (Inhalation)
		H402 – Harmful to aquatic life
Precautionary statements (GHS-US)	:	P201 - Obtain special instructions before use
		P202 - Do not handle until all safety precautions have been read and understood
		P260 - Do not breathe dust, mist, spray, vapors
		P280 - Wear appropriate PPE (See Section 8)
		P308 + P313 - If exposed or concerned: Get medical advice/attention
		P314 - Get medical advice/attention if you feel unwell
		P405 - Store locked up
		P501 - Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards



Vella – Marmorino Finishes (Fine & Coarse)

Safety Data Sheet*

	Date of issue:	11/25/2015	Revision date: 11/25/2015	Supersedes:	Version: 1.0
Other hazards not contributing t classification	othe :	this product. Any exposur OSHA limits. Not Regulate Other constit sprays or pow Particulates TWA and AC	They may be present as residua e to these chemicals during prod Other ingredients may be consi ed. uents in this product are conside vders may cause mechanical irrit Not Otherwise Regulated (Respi	Il trace chemicals in sor uct use is expected to re dered nuisance dusts re red nuisance particles of ation of the respiratory s rable Fraction) has an O Particulates Not Other	DSHA PEL of 5 mg/m ³ (15 mppcf) wise Regulated (Total Dust) has an

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients
--

3.1. Substance

Ş

Not applicable

3.2. Mixture

uct Identifier	%	Classification (GHS-US)
No) 13463-67-7	< 6	Carc. 2, H351 Aquatic Acute 2, H401
No) 14808-60-7	<1	Eye Irrit. 2A, H319 Carc. 1A, H350 STOT SE 3, H335 STOT RE 2, H373
1	No) 13463-67-7	No) 13463-67-7 < 6

Full text of H-phrases: see section 16

1. Description of first aid measures	
First-aid measures general	: Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
First-aid measures after inhalation	Move the affected person away from the contaminated area and remove to fresh air. If breathing problems occur, a certified professional should administer oxygen or CPR if indicated. Seek immediat medical attention.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warn water rinse.
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open. If eye irritation or pain persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Seek medical advice in case of persistent discomfort. Never give anything by mouth to an unconscious person.
2. Most important symptoms and ef	fects, both acute and delayed
Symptoms/injuries	: There are potential chronic health effects to consider.
Symptoms/injuries after inhalation	 May cause cancer by inhalation. Long-term dust, mist, or spray exposure may aggravate pre-existing respiratory disease. Persons who develop silicosis have greatly increased risks of developing tuberculosis and workers who are exposed to crystalline silica and smoke have increased risks of lun damage.
Symptoms/injuries after skin contact	: Direct contact may cause irritation, rash, or dry skin. Rubbing may intensify symptoms and create abrasions.
Symptoms/injuries after eye contact	: Particulate matter may scratch the cornea or cause other mechanical injury to the eye. Scratching or physical damage to the eyes can cause irritation, redness, pain, tear formation, blurred vision, and lig sensitivity.
Symptoms/injuries after ingestion	: Not expected to be a significant route of entry. If ingestion occurs, mild temporary stomach discomfor may result.



Vella – Marmorino Finishes (Fine & Coarse) Safety Data Sheet*

Date of issue: 11/25/2015 Revision date: 11/25/2015 Version: 1.0 Supersedes:

> (silicosis) and increase the risks of developing respiratory cancer. Silicosis is a progressive fibrotic pneumoconiosis which greatly decreases the ability of the lungs toprovide oxygen (decreased pulmonary capacity). The disease may progress even if the worker is removed from exposure. The extent and severity of lung injury depends on a variety of factors including particle size, percentage of silica, natural resistance, dust concentration and length of exposure. Symptoms of silicosis include phlegm, coughing, and characteristic x-rays.

4.3. Indication of any immediate medical attention and special treatment needed

None


.1. Extinguishing media	
Suitable extinguishing media	: Any. Use media appropriate for surrounding fire.
.2. Special hazards arising from	n the substance or mixture
Fire hazard Reactivity	Not flammable.Not reactive under normal use and conditions.
.3. Advice for firefighters	
Protection during firefighting	: Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide adequate protection.

6.1. Personal precautions, protective equi	ipment and emergency procedures
General measures :	Evacuate area. Ensure adequate air ventilation.
6.1.1. For non-emergency person	nel
Emergency procedures :	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment : Emergency procedures :	Equip clean-up crew with proper protection. Stay upwind. Ventilate area.
6.2. Environmental precautions	

Avoid release to the environment

6.3. Methods and material for co	ontainment and cleaning-up
For containment	: Stop leak if you can do it without risk. Contain/dike material for later disposal. Do not touch or walk through spilled material.
Methods for cleaning up	: Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements or confined areas. If necessary (to allow for easy clean-up), absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
	In dry/powder state, completely remove dusts to prevent recirculation of crystalline silica. For small spills, clean with a vacuum with a filtration system sufficient to remove and prevent dust recirculation. For large spills, use a fine spray or mist to control dust creation and carefully scoop or shovel into clean, dry container for later reuse or disposal. DO NOT USE DRY SWEEPING OR COMPRESSED AIR TO CLEAN SPILLS.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed : Precautions for safe handling	Combustion may produce carbon monoxide and other harmful substances. Avoid dust, mist, and spray inhalation. DO NOT use compressed air or dry sweeping to remove dust from work area. Dusts should be removed using an appropriately equipped vacuum. If an appropriate vacuum is unavailable, only wet-clean-up methods should be used (i.e. wet sweeping, misting, etc.). Moisture



7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Containers should be stored in room at ambient temperature and pressure. Keepcontainer closed when not in use.

7.3. Specific end use(s)

Drywall finishing compound

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium Dioxide (13463-67-7)					
USA – ACGIH	ACGIH TWA (mg/m³)	1 mg/m ³			
USA – ACGIH	Remark (ACGIH)	LRT irr; A3			
USA – OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³			

Crystalline Silica (14808-60-7)				
USA – ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ A2		
USA – ACGIH	Remark (ACGIH)	Lung Cancer; Silicosis		
USA – OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ %SiO2+2		
USA – OSHA	OSHA PEL (TWA) (ppm)	250 mppcf %SiO2+2		
USA – OSHA	Remark (US OSHA)	(3) See Table Z-3.		

8.2. Exposure controls	
Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Enclosed processes used in combination with local exhaust ventilation as necessary to control air contaminants at or below acceptable exposure guidelines. Collection systems must be designed and maintained to prevent the accumulation and recirculation of respirable silica into the workplace.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: None required. Polymeric gloves are recommended to prevent irritation. Nitrile construction materials appear to offer the best protection against the ingredients of the product.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Under dusty, misty, spray conditions or when excessive skin contact is likely, wear coveralls or other suitable work clothing.
Respiratory protection	: Wear NIOSH/MSHA approved respirator equipped with particulate cartridges when dusty, misty, or spraying in poorly ventilated areas, and if exposure limits are exceeded. A respiratory program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. For exposures of crystalline silica up to 0.5 mg/m ³ TWA, NIOSH recommends wearing any particulate respirator equipped with an N95, R95, or P95 filter, except quarter-mask respirators.

ECTION 9: Physical and chemical properties				
9.1. Information on basic physical and chen	nical p	properties		
Physical state	:	Semi-solid / Liquid		
Appearance	:	Viscous liquid		
Color	:	Off-white		
Odor	:	Mild characteristic		
Odor threshold	:	No data available		
pН	:	7.5 – 10		
Relative evaporation rate (butyl acetate=1)	:	No data available		
Melting point	:	No data available		

VENETIAN PLASTER SYSTEMS

Vella – Marmorino Finishes (Fine & Coarse) Safety Data Sheet*

	Date of issue: 11/25/2015	Revision date: 11/25/2015	Supersedes:	Version: 1.0
Freezing point	: 0 °C	(32ºF)		
Boiling point	: ~10	0 °C (212°F)		
Flash point	: No c	lata available		
Auto-ignition temperature	: No c	lata available		
Decomposition temperature	: No c	lata available		
Flammability (solid, gas)	: No c	lata available		
Vapor pressure	: No c	lata available		
Relative vapor density at 20 °C	: No c	lata available		
Relative density	: 1.5 -	- 2.0 (water = 1)		
Solubility	: No c	lata available		
Log Pow	: No c	lata available		
Log Kow	: No c	lata available		
Viscosity, kinematic	: No c	lata available		
Viscosity	: 300	– 600 Brabender Units		
Explosive properties	: No c	lata available		
Oxidizing properties	: No c	lata available		
Explosive limits	: No c	lata available		

9.2. Other information

VOC content (VOC of material)	:	< 4 g/L
VOC content for the South Coast Air Quality Management District (SCAQMD) – Regulatory VOC (less water and exempts)	:	< 8 g/L

SECTION 10: Stability and reactivity

10.1. Reactivity

Not reactive under normal use and conditions.

10.2. Chemical stability

Stable at normal temperatures and pressure.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Avoid generating dust, mist, or spray.

10.5. Incompatible materials

Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

Combustion may produce carbon monoxide and other harmful substances.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Not classified

Titanium Dioxide (13463-67-7)	
LD50 dermal rabbit	> 10,000 mg/kg
-	
Skin corrosion/irritation	: Not classified; pH 7.5-10
Serious eye damage/irritation	: Not classified; pH 7.5-10
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (inhalation).

VERTIAN PLASTER SYSTEMS

Vella – Marmorino Finishes (Fine & Coarse)

Safety Data Sheet*

Date of issue: 11/25/2015Revision date: 11/25/2015Supersedes:Version: 1.0

Titanium Dioxide (13463-67-7)		
IARC group	2B – Possib	ly carcinogenic to humans
Crystalline Silica (14808-60-7)		
IARC group	1 - Carcinog	genic to humans
Reproductive toxicity	:	Not classified
Specific target organ toxicity (single expos	ure) :	Not classified
Specific target organ toxicity (repeated exp	oosure) :	May cause damage to organs (lungs/respiratory system) through prolonged or repeated exposure (Inhalation).
Aspiration hazard	:	Not classified
Symptoms/injuries after inhalation	:	May cause cancer by inhalation. Long-term dust, mist, or spray exposure may aggravate pre-existing respiratory disease. Persons who develop silicosis have greatly increased risks ofdeveloping tuberculosis and workers who are exposed to crystalline silica and smoke have increased risks of lung damage.
Symptoms/injuries after skin contact	:	Direct contact may cause irritation, rash, or dry skin. Rubbing may intensify symptoms and create abrasions.
Symptoms/injuries after eye contact	:	Particulate matter may scratch the cornea or cause other mechanical injury to the eye. Scratching or physical damage to the eyes can cause irritation, redness, pain, tear formation, blurred vision, and light sensitivity.
Symptoms/injuries after ingestion	:	Practically non-toxic. Ingestion is not anticipated under normal working conditions.
Chronic symptoms	:	Repeated inhalation of respirable crystalline silica over a number of years can cause lung disease (silicosis) and increase the risks of developing respiratory cancer. Silicosis is a progressive fibrotic pneumoconiosis which greatly decreases the ability of the lungs to provide oxygen (decreased pulmonary capacity). The disease may progress even if the worker is removed from exposure. The extent and severity of lung injury depends on a variety offactors including particle size, percentage of silicosis include phlegm, coughing, and characteristic x-rays.

SECH	UN 12: Ecological informa	
12.1.	Toxicity	
Titani	um Dioxide (13463-67-7)	
EC50	Daphnia	5.5 mg/l Lovern, S.B., and R. Klapper 2006. Daphnia magna Mortality when Exposed to Titanium Dioxide and Fullerene (C60) Nanoparticles. Environ. Toxicol. Chem. 25(4): 1132-1137
12.2.	Persistence and degradability	
	dditional information available	
12.3.	Bioaccumulative potential	
No ad	dditional information available.	
12.4.	Mobility in soil	
No ad	dditional information available.	
12.5.	Other adverse effects	
Effec	t on the global warming	: No known ecological damage caused by this product.
SECTI	ON 13: Disposal considera	tions
13.1.	Waste treatment methods	
Was	te disposal recommendations	 Dispose of as inert solid in landfill. Dispose of waste material according to Local, State and Federal environmental regulations. Never discharge directly into sewers or surface waters. Slurry may plug drains.



Safety Data Sheet*

Date of issue: 11/25/2015 Revision date: 11/25/2015 Supersedes:

SECTION	14: Transport information
	dance with DOT, not regulated for transport.
Addition	l information
	formation : No supplementary information available.
ADR	
No addi	ional information available.
Transpor	t by sea
No addi	cional information available.
Air trans	port
No addi	ional information available.
	15: Regulatory information
	S Federal regulations
	Dioxide (13463-67-7)
Listed 0	n the United States TSCA (Toxic Substances Control Act) inventory
Crystalli	ne Silica (14808-60-7)
Listed o	n the United States TSCA (Toxic Substances Control Act) inventory
15.2. In	ternational regulations
CANADA	
No addi	tional information available.
EU - Reg	Ilations
	ional information available.
Classifica	ntion according to Regulations (EC) No. 1272/2008 [CLP]
Classifica	tion according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]
	at. 2; R22; R43; R49
Full text	of R-phrases: see section 16
15.2.2	. National regulations
Er	nergency procedures : Evacuate unnecessary personnel.
Ti	tanium Dioxide (13463-67-7)
Li	sted on IARC (International Agency for Research on Cancer)
C	ystalline Silica (14808-60-7)
	sted on IARC (International Agency for Research on Cancer)
15.3. U	S State regulations

California - Proposition 65

This product may contain substances known to the State of California to cause cancer: Crystalline silica (airborne particulates of respirable size) and traces of formaldehyde and vinyl acetate monomer. Attapulgite Clay >5µm in length.



Vella – Marmorino Finishes (Fine & Coarse) Safety Data Sheet*

Date of issue: 11/25/2015 Revision date: 11/25/2015 Supersedes:

Version: 1.0

Fitanium Dioxide (13463-67-7)	
J.S. – New Jersey – Right to Know Hazardous Substance List	
J.S. – New York – Reporting of Releases Part 597 – List of Hazardous Substances	
Crystalline Silica (14808-60-7)	
J.S. – Idaho – Non-Carcinogenic Toxic Air Pollutants – Acceptable Ambient Concentrations	
J.S. – New Jersey – Right to Know Hazardous Substance List	
J.S. – Washington – Permissible Exposure Limits – TWA's	
J.S. – Massachusetts – Right to Know List	
J.S. – Pennsylvania – Right to Know List	
J.S. – Rhode Island – Right to Know List	

SECTION 16: Other information

Data sources

: ChemADVISOR, Inc.[https://www.chemadvisor.com]. GESTIS DNEL Database [http://dnelen.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates\$fn=default.htm\$vid=dneleng:ddb eng\$3.0/].

Full text of H-phrases: see section 16:

Acute Tox.3 (Dermal)	Acute Toxicity (dermal) Category 3
Acute Tox.3 (Inhalation)	Acute Toxicity (inhalation) Category 3
Acute Tox.3 (Oral)	Acute Toxicity (oral) Category 3
Acute Tox.4 (Dermal)	Acute Toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 2 (Inhalation: gas)	Acute toxicity (inhalation: gas) Category 2
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable Liquids Category 2
Muta. 2	Germ cell mutagenicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H 341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
R22	Harmful if swallowed
R43	May cause sensitization by skin contact
R49	May cause cancer by inhalation
<u>.</u>	

VENETIAN PLASTER SYSTEMS	Vella – Marm Safety Data Sh Date of issue: 11/25/2015	norino Finishes (Fin neet* Revision date: 11/25/2015	ne & Coarse)	Version: 1.0
		P	-	
NFPA health hazard	•	re could cause irritation but only even if no treatment is given.	/ minor residual	
NFPA fire hazard	: 0 - Materia	als that will not burn.		
NFPA reactivity		ly stable, even under fire exposu e not reactive with water.	ure conditions,	
HMIS III Rating	:			
Health	: 1 Slight	Hazard - Irritation or minor rever	rsible injury possible	
Flammability	: 0 Minim	nalHazard		
Physical	: 0 Minim	nalHazard		
Personal Protection	: E			

SDS US (GHS HazCom 2012)

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of We stpac Materials. The data on this sheet relates only to the specific material designed herein. We stpac Materials assumes no legal responsibility for the use or reliance on this data.