

ASE 9575 DOD 'BEARCAT' DOCK

SECURE YOUR IRIDIUM CONNECTION

- ✔ SUPPORTS BEARCAT SECURE SLEEVE
- ✔ HEADQUARTERS VOICE
- ✔ INTEGRATION WITH OFFICE INFRASTRUCTURE VIA POTS SYSTEM
- ✔ DOD COMPATIBILITY
- ✔ WIDE RANGE INPUT POWER



ASE 9575 DOD 'BEARCAT' DOCK

WHAT'S IN THE BOX?



ASE-9575-HQ-DOD

CONTENTS:

secure sleeve docking cradle with POTS support

wall mount

ac/dc adapter

OPTIONAL ACCESSORIES

ASE-DA12 ASE-DA20

external antenna
Iridium/GPS



ASE-FA12 ASE-FA20

external antenna
Iridium only *

* no GPS features supported



ASE-PT01

POTS phone and mount



ASE MNT03

privacy handset
and swivel mount



ASE-9575-HQ-DOD

ELECTRICAL SPECIFICATIONS

Operating Voltage	10 - 32 VDC
Power Consumption	12 Watts (Avg Active)
GPS Gain Limit	L1: 26-32 dB FREQ: 1575 35 MHZ POL: RHCP BIAS: 3 VDC Cable Impedance: 50 ohm SMA Male

ENVIRONMENTAL SPECIFICATIONS

Operating Temp Range	0°C to +70°C
Exposure	Indoor

MECHANICAL DIMENSIONS

Dimensions	7L x 7W x 5H inches	(18 x 18 x 13 cm)
Weight	2.5 lbs	(1.13kG)
Mounting	Swivel desk or wall mount available	

SHIPPING DIMENSIONS

Dimensions	14L x 10W x 6H inches	(36 x 25 x 15 cm)
Weight	5 lbs	(2.27 kG)