

MCOM1[®]

Comms-on-the-Go!

TECHNICAL SPECIFICATIONS:

MCOM1 H Weight: 24.88 Kg (54.8 lb) with Hughes 9450-C11 in case

MCOM1 H Weight: 15.4 Kg (33.9 lb) without Hughes 9450-C11

Pelican 1600 Outside Dimensions: 24.25" x 19.43" x 8.68"

*Color: Black**

Humidity: 95% RH at +40° C (+104° F)

Temperature: -25° C (-13° F) to +55° C (+131° F) operating

AC Input Voltage: 85-264 AC 47-63Hz

AC Mini Fuse: 6A

DC Input Voltage: 12 V or 24 V systems

DC Fuse: 20A fuses inside DC cigarette power cable, 20A auto blade style in battery clamp power cable

Dual Power Supplies: 150W, Input 85 ~ 264AC, Output 24VDC 6.3A, Universal AC Input / Full Range Protections: Short Circuit / Overload / Over Voltage / Over Temperature / Automatic changeover if one power supply fails

DC inputs are diode protected against operator connection errors

**Optional case and metal colors: Olive Drab & Desert Tan. Additional cost and minimum quantities apply.*



Distributor Information:

HUGHES

inmarsat

MCOM1 H

Professional rugged satellite flyaway to go kit for the Hughes 9450-C11 BGAN Land Mobile Satellite Terminal



MCOM1 H FEATURES

*Housed in the rugged Pelican 1600 Hard Case
Machined aluminum and black powder coated
Internal Dual AC-DC power supplies
Operates on 12/24VDC or commercial AC Power
LED Maplight Red/White, three levels of intensity
Black nylon bag, pouches in lid of case
Protect your investment with a MCOM1 H Ruggedized Tactical Case
Made in USA*

MCOM1 H PACKAGE INCLUDES

*AC power cord 6 Foot (USA)
MCOM1 H DC Battery clamp power cable 12 Foot
MCOM1 H DC Cigarette power cable 6 Foot
9450 DC Cigarette power cable, power cord 6 Foot
(Plugs into 9450 modem)*

