

PC280-7K2



Schuko IP44



CEE32 230V 32A

PC280-7K2

Cable Color	Black
Charging Power (Max)	7.2kW
Input	230V, 6-32A Manually Adjustable
Power Plug	Schuko IP44, CEE32 230V 32A 1-phase
Weight	4.5kg

QUALITY

Screen	3.5 inches
Keying	Mechanical Button
Input Cable	1.3m (Plug Cable 0.5m + Housing Cable 0.8m)
Charging Cable	6m
Charger Size	200 x 90 x 67mm
Housing	Strengthen PC
Connector	Type 2
Operating Temperature	-30℃ to +50℃
Storage Temperature	-30℃ to +60℃
Operating Humidity	5% to 95%
Altitude Limit	< 3000m

SAFETY

Waterproof	IP65	
Residual Current Device	Type A + DC 6 mA With Protective Conductor Monitoring	
Standard	EN IEC 62752:2016+A1 EN IEC 61851 EN IEC 61000-6-1:2019	EN IEC 61000-6-3:2021 EN IEC 62196, RoHS
Safety Protection	Leakage Protection Grounding Protection Over Current Protection Anti-Thunder Protection Over Temperature Protection	Plug Temperature Protection Short Circuit Protection Low Voltage Protection High Voltage Protection
Warranty	2 Years	

AC800 PowerShare Kit



Power Strip (V2L)

Cable Color	Black
Sharing Power (Max)	3.6kW
Output	230V 16A (Max)
Power Socket	3 Socket Outlets, Schuko & CEE 7/7 IP44 Socket
Cable Length	0.5m
Weight	0.4kg
Operating Temperature	-30℃ to +50℃
Storage Temperature	-30℃ to +60℃
Operating Humidity	5% to 95%
Altitude Limit	< 3000m
Remark	The actual sharing power depends on the vehicle's On-Board Charger (OBC)

EV to EV Type 2 Plug (V2V)

Cable Color	Black	Connector	Type 2
Sharing Power (Max)	7.2kW	Operating Temperature	-30℃ to +50℃
Power	230V 32A (Max)	Storage Temperature	-30℃ to +60℃
Weight	0.8kg	Operating Humidity	5% to 95%
Cable Length	0.8m	Altitude Limit	< 3000m
Remark	The actual sharing power depends on the vehicle's On-Board Charger (OBC)		

SAFETY

Standard	EN IEC 62196 EN IEC 62893 RoHS		
Safety Protection (Connected with PC280)	Leakage Protection Grounding Protection Over Current Protection Anti-Thunder Protection Over Temperature Protection	Plug Temperature Protection Short Circuit Protection Low Voltage Protection High Voltage Protection	
Warranty	2 Years		