



Car Roof Tent

INSTRUCTION MANUAL

SPECIFICATION

PRODUCT DESCRIPTION

The Car Roof Tent is the perfect partner for all adventurers. Turn any vehicle into a camper with our easy to install Car Roof Tent. Our Car Roof Tent is the easiest and comfiest way to camp and experience nature.

These Car Roof Tents mount to your vehide's roof crossbars and can be easily deployed in just a few minutes when you find a camp spot. A ladder folds out so that you can climb up into your home away from home, far away from any puddles, insects, and roaming wildlife. Getting back to nature could not be simpler. Pull up, pop-up and camp!

PRODUCT SPECIFICS

FRAME MATERIAL:	Lightweight Aluminium Alloy
LADDER MATERIAL:	Aluminum
TOP SHELL MATERIAL:	ABS Plastic
TENT FABRIC:	280G Polyester Cotton + PU Coating
NET FABRIC:	110g Environmentally Friendly Fixing Gauze
WATERPROOF INDEX:	3000+mm
OPENING SIZE:	213cm×131cm×105cm
WEIGHT:	70KG

ITEM CONTENTS

- 1 tent frame
- 1 ABS case
- 8 screws and nuts
- 1 mattress
- 1 ladder
- 1 condensation pad
- 1 marine blanket
- 1 x fixed storage network
- 2 shoe storage bags
- 1 USB combo
- 1 LED

SPECIFICATION

PRODUCT FEATURES

- A. ABS Shell
- B. Roof Poles
- C. Windows
- D. Door
- E. Ladder



SAFETY ADVICE

SAFE WORKING PRACTICE

Please read through the Safe Working Practice to ensure prevention of injury or damage to the device.

- Do not use this car roof tent for anything other than its intended purpose.
- Please read and understand the instructions prior to using this car roof tent.
- The ladder is only capable of holding one person at a time. The load capacity is 150kg.
- Do not place heavy objects on to the ladder.
- Do not allow children to use the tent or ladder without adult supervision.
- Do not use the car roof tent in high winds.
- To avoid injury to yourself or others always take care when using the ladder. Do not jump from the ladder.
- Always empty the tent before folding close.
- Before driving with the roof tent, always check your roof rack and your car roof tent are securely attached to the vehicle and tighten any nuts or bolts if needed.
- Do not smoke or use a naked flame while in the tent.
- Do not attempt to overload the tent. The maximum load for the tent frame is 300kg.
- Only attach the car roof tent to a suitable roof rack . Your roof load capacity must be 75kg or more.
- Get advice from a specialist roof rack retailer. They'll have a database to find racks that are suitable for your model vehicle and compatible with a rooftop tent.
- Always clean the ladder rungs to reduce the chances of slipping while ascending or descending.
- Do not exceed 70 mph (110 km/h) when you have the roof tent attached to your car.
- Ensure you have installed the roof rack safely as per the manufacturer's instructions, is authorised for use with your vehicle, and has an adequate load capacity.
- Be aware that your vehicles height will increase when the car roof tent is installed. Take care with low entrances and low-hanging branches.
- Be aware that your vehicles driving characteristics will change when the car roof tent is installed.
- Do not place items on top of the roof tent when it is on your vehicle.

USER GUIDE

INSTALLATION INSTRUCTIONS

1

Before fitting your car roof tent, please check that your roof rack is suitable. This car roof tent is designed to be fitted to lengthways roof racks with a minimum distance of 3cm between the roof rack and the car roof.



2

Insert screws into the holes at each end of the four-eyed gaskets and slide into the slots under the roof tent.



3

Adjust the tent to the appropriate position on the car roof. Remember not to obstruct the boot lid.



USER GUIDE

INSTALLATION INSTRUCTIONS

4

Use another piece of four-eye gasket with the nut for fastening. Please note, when the distance between the roof rack and the car roof is less than 4 cm, the short bolts will be used instead of the long bolts.



5

The installation is now complete, and you are ready to go!



USER GUIDE

OPERATION INSTRUCTIONS

①

To set up the Roof Tent, undip the buckle.



②

Push the upper part of the ABS hard shell on one side and it will automatically bounce off.



③

Push the ABS hard shell on the other side and the whole tent will be opened.



④

Your tent now is fully erect.



USER GUIDE

OPERATIONS INSTRUCTIONS

5

Insert support bars at the bottom of windows and curtains.



6

Use spring bars to hold windows and curtains open.



7

To extend the ladder, hold the lowest rung of the ladder and then pull the ladder.



8

Remember to adjust the ladder to a suitable height. The ladder must be at an angle of 75 degrees when using the ladder.



USER GUIDE

FOLDING INSTRUCTIONS

First, unzip all the windows and doors and remove any contents from the tent.

Press down on the tent roof and the whole tent will fold into its shell.

To fold up the ladder, press the button on the bottom rung of the ladder to release the lock. Firmly push the ladder from the bottom rung until it is completely folded in. You can now slide it under the roof tent.

Lastly, fasten the buckles around the bedframe.

USER GUIDE

MAINTENANCE

Follow these steps to keep your Car Roof Tent in top condition.

- Use a damp cloth to wipe excess dirt from the tent after each use.
- Do NOT use bleach, alcohol or ammonia based cleaning fluids on your car roof tent as these will damage the tent material.
- Always remove any excess water from the fabric before folding up.
- Do NOT use a heat source to dry the tent, allow to dry naturally.

TROUBLESHOOTING

RESOLUTION GUIDE

WHAT DO I DO IF THERE ARE MISSING PARTS FROM MY ORDER?

If there appears to be any part missing from your order, contact our friendly and helpful Customer Support Team within 7 days of receipt.

WHAT DO I DO IF I CAN NOT OPEN THE CAR BOOT LID AFTER INSTALLING THE TENT?

You can adjust the position of the Car Roof Tent. If the tent is obstructing the boot lid, loosen the gaskets holding the Car Roof Tent to the roof rack and slide the Car Roof Tent forward.

FOR ALL OTHER ISSUES, PLEASE CONTACT OUR
CUSTOMER SUPPORT TEAM.

