

— CLICK MODEL NAMES IN TOP ROW OF CHART TO VIEW PRODUCTS —

(Viewing on mobile device? Turn it sideways for optimal display.)

SHOP COFFEE GRINDERS

MODEL	DITTING 807 RETAIL	DITTING 807 FILTER	DITTING 807 LAB SWEET	DITTING KRI203	DITTING KRI403	DITTING KFA1403	MAHLKÖNIG GH2	MAHLKÖNIG GUATEMALA 2.0	MAHLKÖNIG EK43 FILTER	MAHLKÖNIG EK43S (SPACE SAVING)	MAHLKÖNIG E65S ESPRESSO	MAHLKÖNIG E65S GbW	MAHLKÖNIG E80 SUPREME ESPRESSO	MAHLKÖNIG E80 GbW
PHOTO														
FOR USE IN	Small cafes	Small cafes	Cupping labs, pour-over bars, small cafes	Large cafe w/heavy traffic	Large cafe w/heavy traffic	Roasting areas, higher volume grinding	Shops, roasteries, labs	Shops, roasteries, labs	Shops, roasteries, labs	Shops, roasteries, labs	Shops, roasteries, labs	Shops, roasteries, labs	Shops, roasteries, labs	Shops, roasteries, labs
OUTPUT, lbs/min	2 lbs/min	2 lbs/min	2 lbs/min	5 lbs/min	6 lbs/min	6 lbs/min	1 lb/min	Just under 2 lbs/min	3.3 lbs/min	2.4-3 lbs/min	2-3 double shots/min	2-3 double shots/min	5-6 double shots/min	10 double shots/min
MAX DAILY OUTPUT, lbs (8-hr shift)	Up to 106 lbs/day	Up to 106 lbs/day	Up to 106 lbs/day	Up to 500 lbs/day	Up to 1,000+ lbs/day	Up to 1,000+ lbs/day	Up to 320 lbs/day	Up to 640 lbs/day	529 lbs/day	529 lbs/day	N/A	N/A	N/A	N/A
MAX OPERATING CYCLE	180 sec on; 300 sec off (3 min on; 5 min off)	180 sec on; 300 sec off (3 min on; 5 min off)	180 sec on; 300 sec off (3 min on; 5 min off)	Continuous grinding	Continuous grinding	Continuous grinding	40 min on; 20 min off	40 min on; 100 min off	40 min on; 100 min off	40 min on; 100 min off	110-127V: 5 sec on; 25 sec off 220-240V: 5 sec on; 15 sec off	110-127V: 5 sec on; 25 sec off 220-240V: 5 sec on; 15 sec off	100V: 3 sec on; 3 sec off 110-127V: 3 sec on; 3 sec off 220-240V: 3 sec on; 3 sec off	100V: 3 sec on; 3 sec off 110-127V: 3 sec on; 3 sec off 220-240V: 3 sec on; 3 sec off
HOPPER CAPACITY	1 lb	1 lb	1 lb	2.4 lbs (Optional 5-lb extender)	2.5 lbs (Optional 5-lb extender)	22 lbs	4.4 lbs	4.4 lbs	3.3 lbs	3.3 lbs	2.6 lbs	2.6 lbs	3.97 lbs	3.97 lbs
GRINDING INTO	Coffee bag	Filter, coffee basket	Filter, coffee basket	Barrel, large container	Barrel, large container	Barrel, large container	Bag, brew basket	Bag, brew basket	Bag, brew basket	Bag, brew basket	Portafilter	Portafilter	Portafilter	Portafilter
GRIND RANGE	130 to 1,400µm	130 to 1,400µm	100 to 1,200µm	300 to 900 µm	200 to 1,100 µm	200 to 1,100 µm	Coarse to Turkish Fine	Coarse to Turkish Fine	Coarse to Turkish Fine	Coarse to Turkish Fine	Coarse to Turkish Fine	Coarse to Turkish Fine	180 to 600 µm	150 to 450 µm
FEATURES	Adjustable Spout Vibration Shaker Plate Bag Shaking Unit	Bag Shaking Unit Automatic Bag Clamp	Automatic Bag Clamp	Bag Shaking Unit Manual Bag Clamp	Bag Shaking Unit Manual Bag Clamp	Extended Chute; Automatic Bag Clamp	Adjustable spout w/bag holder Removable grind tray	Height-adjustable, removable table Spout with bag clamp Vibration shake plate	Bag clamp, slide plate	Bag clamp, slide plate	Adjustable, removable spout; Universal portafilter holder	Active internal cooling system; 5" high-res display; grind flow control; adjustable illuminated grind chute	Adjustable, removable spout; 5" high-res display; universal portafilter holder; 6 programmable recipes	Adjustable, removable spout; 5" high-res display; universal portafilter holder; 6 programmable recipes
POWER	120 V / 60 Hz / 1~	120 V / 60 Hz / 1~	120 V / 60 Hz / 1~	120 V / 60 Hz / 1~	220V / 60Hz / 3~	220V / 60Hz / 3~	100-115 V / 60 Hz / 1~	100 V / 50-60 Hz / 1~ 100-127 V / 60 Hz / 1~ 220-240 V / 50-60 Hz / 1~	100-120 V / 50/60 Hz / 1~	100-120 V / 50/60 Hz / 1~ 200-240 V / 50/60 Hz / 1~	100 V / 50-60 Hz / 1~ 100-127 V / 60 Hz / 1~ 220-240 V / 50-60 Hz / 1~	100 V / 50-60 Hz / 1~ 100-127 V / 60 Hz / 1~ 220-240 V / 50-60 Hz / 1~	100 V / 50-60 Hz / 1~ 100-127 V / 60 Hz / 1~ 220-240 V / 50-60 Hz / 1~	110-127 V / 60 Hz / 1~ 220-240 V / 50/60 Hz / 1~
GRINDING DISC DIAMETER & MATERIAL	80mm (3.2") Special steel	80mm (3.2") Special steel	80mm (3.2") Cast steel	120 mm (4.7") Special steel	140 mm (5.5") Special steel	140 mm (5.5") Special steel	85 mm (3.3") Special steel	71 mm (2.8") Special steel	98 mm (3.9") Special steel	98 mm (3.9") Special steel	65 mm (2.6") Special steel	65 mm (2.6") Special steel	80 mm (3.2") Special steel	80 mm (3.2") Special steel
COLORS	Black, White	Black, White	Black, White	Black, Stainless	Black, Stainless	Black	Black	Black	Black, White	Black, White	Black, White	Black, White	Black, White	Black, White
CERTIFICATIONS	CB, UL/CSA, NSF, KTL, EAC	CB, UL/CSA, NSF, KTL, EAC	CB, UL/CSA, NSF, KTL, EAC	CE, CB, UL, NSF	CE, CB, UL, NSF	CE, CB, UL, NSF	CE, ETL, NSF	CE, CB, ETL	CE, CB, ETL	CE, CB, ETL	CE, CB, ETL	CE, CB, ETL	CE, CB, ETL	CE, CB, ETL
DIMENSIONS DxWxH, inches	11.2" x 8.5" x 21.1"	11.2" x 8.5" x 21.1"	11.2" x 8.5" x 21.1"	13.3" x 10.2" x 26.2"	13.3" x 10.2" x 26.2"	13.3" x 10.2" x 26.2"	26" x 7" x 17"	13" x 8.7" x 24.5"	16.2" x 9.1" x 32.7"	16.2" x 9.1" x 32.7"	18.7" x 7.7" x 11.3"	18.7" x 7.7" x 11.3"	25" x 9.5" x 13.5"	18.8" x 27.4" x 11.3"
WEIGHT, lbs	38 lbs	40 lbs	38 lbs	84 lbs	84 lbs	84 lbs	57 lbs	62 lbs	54 lbs	54 lbs	27 lbs	27 lbs	39 lbs	40 lbs
WARRANTY	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year