

Description

Self priming, pneumatic pump with integral heater designed for wet glue labelling adhesives on labelling stations. It is suitable for use on Krones, Langguth and other labeller types for warming up the glue prior to application. By heating the adhesive, it ensures consistent viscosity of adhesive at point of application, ensuring

Ancillary equipment for bottling and packaging lines:

- Adhesive pumping systems
- Wet glue warming systems
- Hot melt nozzles and filters

The Birkstein Otlar Heated Glue Pump will ensure your adhesive is applied at a consistent temperature all year round, ensuring you get a consistent even glue application regardless of factory temperatures – this ensures you get the following benefits:

- Glue Consumption Savings
- No Build up on machine parts
- No Spitting from the roller
- Consistency of glue application
- Better Quality Labelling with excellent label lay-flat properties



Specifications

Weight	6.9kg	Air Consumption	170l/min @ Max
Length	742mm	Operating Pressure	3-6 bar
Voltage	240/60/110	Temperature Controller	Display
Heater Output	950W	Protection Class	IP66: Protected from dust and high-pressure water jets from any direction
Pump Capacity	240l/h	Warranty	12 Months*
Stroke Speed	2Hz	Birkstein Otlar Product Code	Bars: 044 001 03 No Bars: 044 001 05
Max Viscosity	100,000mPas		
Temperature Range	50°C Max		

*On non-wearing parts under normal conditions