



Adhesive Type: Hot Melt Adhesive

Grade Reference: FastLock® 71P

## How to Apply

FastLock® 71P is a hot melt stick for general packaging operations with a fast-setting time and medium viscosity. This allows FastLock® 71P to be used on a variety of paper and board materials. Most 12mm applicator guns are suitable for this product.

Storage: Keep the containers closed, cool and dry. The shelf life is 2 years

## Technical Information

<b>Adhesive type</b>	Synthetic polymer-based hot melt
<b>Brookfield viscosity</b>	4500cP at 180°C ± 500cP
<b>Ring and ball softening point</b>	99°C ± 5°C
<b>Adhesive open time</b>	Medium
<b>Colour</b>	Yellow-ish
<b>Recommended working temperature</b>	180°C - 210°C
<b>Form</b>	Stick 11.5mm x 300mm
<b>Packaging</b>	10Kg boxes

FDA approved: all the constituent parts of this adhesive have been approved by the American FDA under CFR 21.175.105

The information given and the recommendations made herein are based on our current experience and are believed to be accurate. No guarantee as to, or responsibility for, their accuracy can be given or accepted and no statement made herein is to be treated as a representation or warranty. In every case we urge and recommend that purchasers before using any products make their own tests to determine, to their satisfaction, it's suitable for their particular purposes under their own operating conditions. Such an evaluation should be repeated if materials are changed in any way or brought from a different source. No agent or representative of Alphabond has any authority to vary, omit or otherwise alter these terms.

Alphabond Technologies Ltd | UK Technical | Telephone: 0044 (0)845 5212057 | Web: [www.alphabond.com](http://www.alphabond.com)