V1XS Document Camera



12X Optical Zoom 10X Digital Zoom

- Equipped with 12X optical zoom lens that adjustable by stepless knob.
- Foldable design and able to capture A3 size image.
- Ultra smooth video performance: 1080P/60 fps.
- Document or object could be easily magnified in touching. control UI and previewed on the 5" LCD screen as well.



More Details



Total 120X Zoom

12X Lossless Optical Zoom & 10X Digital Zoom.



Full HD 1080P/60fps

Smooth HD image captured by 8.0MP CMOS sensor.



5" LCD Preview Screen

5 " LCD screen with full UI, picture preview and location can be easily came true.



Touch Button

Scratch resistant armored glass, sensitive and quick responce.



Stepless Control Knob

Turning knob to zoom-in/out and select in PC free mode.



PC/PC Free Software

freeze, record, etc.



Built-in LED Lights

Strong clarity images can be displayed even in dimly lit environment.



USB/HDMI/VGA Interface


Support PC, projector, touch screen, interactive board and other display devices.





Compact, foldable design

Compact design makes it ideal for space-constrained classrooms or for summertime storage.



Large Image Shooting Area

With A3 shooting area, you can share information more flexibility.

Technical Parameter

HARDWARE

- Sensor : Sony 1/3.2" 8M CMOS
- Resolution: 3264*2448
- Frame Rate: 60fps maximum
- Optical Zoom: 12X
- Digital Zoom: 10X
- Lens: F=1.5
- Shooting Area: Max A3 (297mm * 420mm)
- Power Supply: 12V/1A
- Focus Model: Auto focus
- Illumination System: White LEDx1
- LCD: 5" LCD display for preview, resolution 1280*720
- MIC: Built-in mic
- Rotation: 90° 180° 270°
- Stepless control knob: AF / OK. Zoom in / out
- **Touch Button:** freeze/unfreeze,rotate, recording, snap, back, Menu, light, signal source.

DIMENSIONS & PACKAGE

- Height x Width x Depth:
- 11.14["] (283 mm) x 5.43["] (138 mm) x 18.66["] (474 mm)
- Net / Gross weight: 2.93kg / 4.88kg

INISIDE THE BOX

- Joyusing V1XS Document Camera
- AC power adapter with power cord
- USB Cable
- VGA Cable
- HDMI Cable
- Warranty Card
- Quick Start Guide
- Application software CD

INTERFACES

• HDMI IN/OUT, VGA IN/OUT, LINE IN/OUT, SD 3.0, USB

Software Overview



Split Screen

Two windows, one for static images, the other for dynamic images, which supporting drag, zoom in and zoom out.




Picture-In-Picture

Main window aims to display something working on and the assistant window switch what you want to display. Both two can be switched freely.



Annotation

Taking the real-time pictures directly, or notations can be come first, and then taking annotated pictures.




Reading Assist

Cover and high-light mode contribute to better reading, such as data magazines, documents, etc.



Super Zoom

Max.up to 120X, catching all the details perfect.



Freeze

Touching the freeze button, the screen can be instant frozen unless you touch it again to cancel it.



Record HD Vedio

Recording 1080p/ 60FPS, any output specification can be choosed.



Rotation and Mirror

Lens rotation 90, 180, 270, 360°, the image can be adjusted horizontally and vertically for better mirror.



Image Adjustment

The shooting mode of text and portrait modes can be choosed which depend on what you want to shoot.

Suppose th	oca		*ce of spheroi
d PC are pa	Import File	5. If measure (a) matrices $n+n-10$, and $\forall n+0^{-1}$, point $P_n(n,n)$ matrices the vector $\overline{P_nP_{n-1}}=0$, \overline{D} , and $\overline{S}_n=n+n_1+\cdots+n_n$, then $S_n=(-)$. As a 1 Ref. Const. D	hen the volu
ne superfic	WORD EXCEL TEXT	A TTI BAY LOTTO BLANT. TA A THOMSE THE F. A.B. and C. est four points on the surface of subworld 0. FA, FB and K are point wine perpendicular/BED, and FM/PPOL. Then the volume and the material summariants of the subscender/DE requestionly raises $(M^{2} - M^{2}) = 2M^{2} + M^{2}$. In the subscender of the subsce	ely(分别) are
$(A)V = \frac{\gamma}{2}$	Language Identification S English	$(dF = \frac{1}{2}g_{ij}g_{ij}^{-2} + bit = (DF = \frac{1}{2}g_{ij}g_{ij}^{-2} + bit)$ $((T = \frac{1}{2}g_{ij}g_{ij}^{-2} + 2g_{ij}^{-2} - (DF = \frac{1}{2}g_{ij}g_{ij}^{-2} + 2g_{ij}^{-2})$ TWO. Fit in the binade with proper suprocess (COI-orbitabile) 7. Noval (CII). Conservation (EVI (G = 2g_{ij}^{-2} + 2g_{ij}^{-2} - 2g_{ij}^{-2} + 1/2))))	
(C)V = -	American Renetican	the value means of real ander a in	
O. Fill in th	Bulgarian Caculan	$x^2 + x + 1 > 2x + x$ be along true, then the value range of x is 19. Shows that real mashers x , y are satisfying conditions $\begin{cases} x + 2 \ge 0 \\ y - 2y + 2 \ge 0 \\ z - z \end{pmatrix}$.	
For all $x \in \mathbb{R}$	Croatian Carech	than the machines of "atthe-y in	ays true, then
e value rar	Darish Datch		1
The solut	OCR Recognizing	Last page Next Page	

9. For all $a \in \mathbb{R}$ satisfying $|a| \leq 2$, let the range of values of x of the

OCR

Selected content can be OCR based on TEXT shooting mode with editable documents, such as PDF, WORD, TEXT and EXCEL.



Multiple Languages

Chinese, English, Spanish, German, Korean, French, Italian, Dutch etc. Support OEM.

Website





Joyusing Technolofy Co.,Ltd

 Website:
 www.joyusing.com
 Online Store:
 store.joyusing.com

 Email:
 sales@joyusing.com
 Address:
 Floor 18th-19th, Building NO.20, Haixi Innovation Science Park, Fuzhou, Fujian 350108, China