

SF 150™

Welding



STANDARD	BACKREST	
	2" height adjustment «Floating without interval »	
	Backrest adjustment range 12" to 14"	
	Ergonomic padded backrest (12,75"w x 6,5"h)	
	SEAT	
	High resilience velva foam	
	Profiled seat (12,5"w x 12"d x 2"h)	
	SEAT HEIGHT AJUSTMENT	
	Cylinder 140 mm (18"-23")	
	MECHANISM	
Backrest adjustment		
Seat height adjustment		
BASES		
28" industrial steel		
CASTERS / GLIDES		
3" rubber casters (slow rolling)		

OPTIONS	SEAT	
	Profiled seat (17"w x 16"d x 2"h)	
	SEAT HEIGHT ADJUSTMENT	
	Cylinder 80 mm (15,5"-18,5")	
	Cylinder 100 mm (16,5"-20,5")	
	CASTERS / GLIDES	
	3" rubber casters with brake (slow rolling)	
	3" double rubber casters (fast rolling)	
	3" double rubber casters with brake (fast rolling)	
	2" glides	
3" glides		

OPTIONS ADDITIONNELLES	Memory foam (seat)
	Memory foam (backrest)
	Tool compartment (11"w x 6"d x 1"h)
	Tool compartment (19"w x 8"d x 1"h)

SPECIAL NEEDS
COMPUTERS
1-877-724-4922