

# TF 150™

## Welding



<b>STANDARD</b>	<b>BACKREST</b>	
	2" height adjustment «Floating without interval »	
	Backrest adjustment range 12" to 14"	
	Ergonomic padded backrest (12,75"w x 6,5"h)	
	<b>SEAT</b>	
	High resilience velva foam (12,5"w x 9"d x 2"h)	
	Profiled seat (12,5"w x 12"d x 2"h)	
	<b>SEAT HEIGHT ADJUSTMENT</b>	
	Cylinder 200 mm (20,5"-28,5")	
	<b>MECHANISM</b>	
Seat height adjustment		
Seat angle adjustment		
<b>BASES</b>		
28" industrial steel base		
20" footrest (adjustable height)		
<b>CASTERS / GLIDES</b>		
3" rubber casters (slow rolling)		

<b>OPTIONS</b>	<b>SEAT</b>	
	Large format(17"w x 16"d x 2"h)	
	<b>SEAT HEIGHT ADJUSTMENT</b>	
	Cylinder 270 mm (24"-34")	
	<b>CASTERS / GLIDES</b>	
	3" rubber casters with brake (slow rolling)	
	3" double rubber casters (fast rolling)	
	3" double rubber casters with brake (fast rolling)	
	2" glides	
	3" glides	

<b>ADDITIONAL OPTIONS</b>	Memory foam (seat)
	Memory foam (backrest)
	24" footrest (adjustable height)
	Tool compartment (11"w x 6"d x 1"h)
	Tool compartment (19"w x 8"d x 1"h)

**SPECIAL NEEDS**  
**COMPUTERS**   
**1-877-724-4922**