


Dealer/Contractor Company _____ Contact Name _____


Customer Name or Reference or PO ID: _____ Date _____

Address _____ City _____ State _____ Zip _____


Phone _____ Email _____




Left Hinges +
Inward Swinging



Right Hinges +
Inward Swinging



Left Hinges +
Outward Swinging



Right Hinges +
Outward Swinging

(Looking at the door from the inside)

MOUNTING FORMATS

- Door Mount – Inward opening doors/ Pulls Door Open
(Unit mounted to door and arm pushes against frame, pulling door open)
- Lintel Mount – Outward opening doors
(Unit Mounted to frame and arm pushes door outward)
If door is recessed in frame, indicate depth of recess (inches): _____
- Parallel Mount – Outward opening doors & need/want a wider opening angle; storm door application

APPLICATION TYPE

- Interior Door
 Exterior Door
 French Door
 Storm Door
 Screen Door

DOOR DETAILS

1. Location of door? _____

2. Door Material Wood Steel Aluminum

Note: Door mount unit on light hollow door will require thru bolts or structural stiffening

3. Door Frame Material Wood Steel Aluminum

4. Door Height: _____ Door Width: _____

5. Distance to Ceiling from the Top of the Door Frame? Outside: _____ Inside: _____

6. Is there enough clearance above door to install lintel mount unit? Yes No

Requires at least 4" above top of door

7. Distance from wall to door when door is open at 90° _____

Door mount unit requires at least 2 5/8" between inside door surface and wall

OPEN SESAME DOOR SYSTEMS, INC.

DOOR DETAILS continued

8. Reveal (distance from back surface of unit to face of door _____)

Reveal for standard lintel mount is ½" to 4 ½"; deep reveal unit is 4 ½" to 9 ½"

9. Type of hinges Butt Swing Clear Center Pivot/Offset Pivot

10. Is door closer suitable for reversing to other side of door? Yes No

11. Is an electric door strike required? Yes No

Strike required for: Spring Latch Deadbolt Latch & Deadbolt Combination(Mortise Lock)

12. Is 115VAC receptacle within 30'? Yes No

13. For French Door applications, activate Single Door Both Doors

Test: Open door and using your pinky finger push the door closed

14. Are you able to close the door? Yes No

15. Is there any weather stripping on the door? Yes No

16. Is there any dragging on the door? Yes No

NOTE: If the door is dragging, has thick weather stripping, or has any issues closing smoothly, this will need to be fixed before installing Open Sesame unit or it will not work properly.

ORDERING INFORMATION

Residential Bundle

M133 Operator
A-R 7440 Electric Strike
One Remote Control
Transformer/Wiring Kit
Remote Choice: (C) (D) (H) (I)

French Door Bundle

M133 Operator
Trine 3234 Strike: Wood or Metal
One Remote Control
Transformer/Wiring Kit
Remote Choice: (C) (D) (H) (I)

Residential Bundle Autoslide

M133 Operator
A-R 7440 Electric Strike
Transformer/ 6-Wire Wiring Kit
Proximity Sensor System (w/ 2 tags)

ScreenDoor/Storm Door

M233 Operator
Long Screw Spacer
Transformer/Wiring Kit
Drop Plate: A or B

Model 133 Operator Only

Operator Color Choices: Antique White Dark Bronze Silver

Accessories:

- | | | |
|--|--|--|
| <input type="checkbox"/> (B) E.C.U. Remote | <input type="checkbox"/> (FL) Large Wall Pushpad | <input type="checkbox"/> Tash Switch Mini-cup |
| <input type="checkbox"/> (C) Keychain Remote | <input type="checkbox"/> (FT) Wall Touchpad | <input type="checkbox"/> Blow Switch Unit |
| <input type="checkbox"/> (D) Standard 1-Button Transmitter | <input type="checkbox"/> (FW) 36" Vertical Pushpad | <input type="checkbox"/> A-R 7440 Strike |
| <input type="checkbox"/> (E) Keyless Entry Pad | <input type="checkbox"/> (H) 2-Button Transmitter | <input type="checkbox"/> HES 1006 Strike |
| <input type="checkbox"/> (FN) Narrow Wall Pushpad | <input type="checkbox"/> (I) 4-Button Transmitter | <input type="checkbox"/> Trine 3234/3234W Strike (metal or wood) |
| | <input type="checkbox"/> Proximity Sensor System | |