

HAWK Mighty 13 & Mighty 15 Small Area Floor Machines



Stripping, Scrubbing, Polishing

Machine operators will appreciate the performance, versatility and value in the HAWH Mighty. The 1.0 HP TEFC (Totally Enclosed Fan Cooled) AC motor and XHD gears deliver huge power in a small and manageable machine. The Mighty is ideal for use in tight spaces, restrooms, edging and stairs.

The HAWK Mighty innovative design incorporates a state of the art "World Motor" works around the globe without modification .

Power

- 1.0 HP. TEFC AC Motor
- 115-230V, 50/60 Hz power
- 50 ft., (14-3) 2-piece commercial power cord with cord lock

Drive System

- Triple-planetary severe-duty 11:1 helical-cut industrial gears, case hardened with steel coupler
- Gears drive brushes and pads at 165 RPM

Engineered Design

- · All steel construction with welded, powder-coated frame
- Telescoping handle (TH models) adjusts from 36" to 48"
- Brush covers have full wraparound bumper
- One piece powder-coated, heavy-duty steel handle with 6-position pin lock
- · Comfortable vinyl dipped foam handle grips
- Thumb-operated safety switch. Negative pressure on/off switch
- · Dual steel operating triggers
- 1" x 5" non-marking ball bearing wheels
- · Optional dust collection kit
- Optional handle mounted cord wrap (#KIT3009-1BLK)
- Optional 4 gallon solution tank (#A0001-Color4)

Safety Features

- Quiet 64 dB operation. Meets GS42 standard.
- Built with UL Listed components

| Specifications | | | | | |
|----------------|-----------|--------------|-----------|--------------|--|
| Model | MIGHTY 13 | MIGHTY 13-TH | MIGHTY 15 | MIGHTY 15-TH | |
| Item # | F60-13 | F60-13TH | F60-15 | F60-15TH | |
| Handle | Rigid | Telescoping | Rigid | Telescoping | |
| Size | 13" | 13" | 15" | 15" | |
| Pad Size | 12" | 12" | 14" | 14" | |
| Pad Speed | 165 RPM | 165 RPM | 165 RPM | 165 RPM | |
| Amp Draw | 4.9 | 4.9 | 6 | 6 | |
| Weight | 87 lbs. | 87 lbs. | 88 lbs. | 88 lbs. | |
| | | | | | |

All Models

| Motor | 1.0 HP, TEFC AC |
|--------------------|--|
| Power Source | 115-230V, 50/60 Hz |
| Power Cord | 50 ft., (14-3) 2-piece commercial with cord lock |
| Gear Box | Triple-planetary XHD 11:1 helical-cut industrial |
| Sound Level (ave.) | 64 dB - Meets GS42 standard |

Subject to Change Without Notice



Tight Spaces



Telescoping Handle Adjusts from 36" to 48"



Optional 2.5-Gallon Solution Tank



Handle with 6-Position Pin Lock