

THE ORIGINAL
FATSAC
 BALLAST BAG CO.

Barefoot International & Fat Sac Mfg.
 3879 North Richards Street
 Milwaukee, WI 53212

PHONE 414-964-3668 ■ FAX 414-964-5767 ■ E-MAIL orders@fatsac.com ■ WEB www.fatsac.com



PART#	DESCRIPTIONS * Fittings Used with W709-SUPAPump* •Fittings made for automatic ballast systems•
W720	EPOXY CEMENT FOR FITTINGS, 25ML OR 1 OZ TUBES (AKA:50805) — MIX WELL BEFORE USE!
W730 *	SUPA PUMP QUICK CONNECT W/ TETHER & CAP — USED FOR FILLING FATSACS
W739 *	SUPA PUMP QUICK CONNECT CAP ONLY
W731	FAT SAC PLUGS — SAC VALVE THREADS MALE
W732	FEMALE GHT (GARDEN HOSE THREAD) — MALE QUICK CONNECT - FILL FATSACS WITH GARDEN HOSE
W733-SS •	1" BARBED END — SAC VALVE THREADS MALE — SHOULD USE PERMANENT EPOXY CEMENT (W720)
W734 *	SUPA PUMP QUICK CONNECT — FOR WATER INTAKE ON BOTTOM OF SUPA PUMP
W772	HEYCO NYLON 6/6 AUTO AIR BLEEDER VALVE
W736-SS •	3/4" QUICK CONNECT — SAC VALVE THREADS — SHOULD USE PERMANENT EPOXY CEMENT (W720)
W737 •	3/4" BARBED END — SAC VALVE THREADS — SHOULD USE PERMANENT EPOXY CEMENT (W720)
W738 *	SUPA PUMP QUICK CONNECT — 1-1/8" BARBED FITTING - GOES ON END OF SUPA PUMP HOSE
W740 •	FLOW-RITE 3/4" STRAIGHT QUICK CONNECT SOCKET
W741 •	FLOW-RITE 1-1/8" STRAIGHT QUICK CONNECT SOCKET
W742 •	FLOW-RITE 3/4" ELBOW QUICK CONNECT SOCKET
W746 •	FLOW-RITE 1-1/8" ELBOW QUICK CONNECT SOCKET
W743-DOUBLE •	DOUBLE SIDED 1-1/8" QUICK CONNECT FITTING
W743-SS •	1-1/8" QUICK CONNECT - SUCTION STOP SAC THREADS — USE PERMANENT EPOXY CEMENT (W720)
W744 *	1 WAY CHECK VALVE FOR SUPA PUMP
W774	INFLATION VALVE WITH 3/4" NPT MALE SAC THREADS (FOR FILLING FATSACS WITH AIR)
W748 •	1-1/8" QUICK CONNECT TO 1" BARBED
W749	AIR RELEASE PLUG — TURN TO RELEASE AIR. FOR MANUAL AIR VENTING.
W753 •	1" BARBED IN-LINE CHECK VALVE
W755 •	1-1/8" BARBED IN-LINE CHECK VALVE
W729 *	FEMALE PUMP QUICK CONNECT - MALE SAC VALVE THREADS - THE BOTTOM OF THE W730 FITTING
W743-REGAL	1-1/8" QC FITTING WITH 1/2" NPT THREADS (USED W/ S2002 JOHNSON PUMP 13.5 GPM) FOR HOSE
S1004 •	FLOW-RITE 90 DEGREE ELBOW THRU HULL FITTING (BARBED END)
S1003 •	FLOW-RITE STRAIGHT THRU HULL FITTING (BARBED END)
S1007	1-1/2" FLOW-RITE QUICK CONNECT ELBOW FITTING (FITS W775 QC)
S1008	1-1/2" FLOW-RITE QUICK CONNECT STRAIGHT FITTING (FITS W775 QC)
S1006	1-1/2" X 12 UNF QC HF TALLULA PUMP FITTING (FITS S2001 30GPM PUMP) FOR ATTACHING HOSE
S1005	FAT SAC SOCKET SPLITTER + USB PORTS + ON/OFF SWITCHES (RUN 2 PUMPS W/ 1 CIG. ADAPTER)
W746-PLUG •	FLOW-RITE 1-1/8" PLUG FITS INSIDE W746/W741 FITTINGS TO CAP OFF PNP SYSTEMS IN BOATS

IMPORTANT: Use Permanent Epoxy Cement W720 on the threads of the W733-SS, W736-SS, W737, W743-SS, and W747 when screwing them into Fat Sacs.
 DO NOT USE PLUMBERS TAPE OR PLUMBERS PUTTY IT WILL VOID WARRANTY!

NEW! SUPA TSUNAMI PUMP UPDATE (W709-SUPA)



JUICED EDITION

- [1] Most lightweight, user friendly, and fastest system from start to finish
- [2] Quick connect valve for fill & empty
- [3] 12 volt plug & play
- [4] New clear reinforced, kink-proof, black helical, tiger hose

QUICK TIPS FOR USING THE SUPA TSUNAMI PUMP (W709-SUPA)

STEP 1: First put the Supa Tsunami Pump over the side of the boat under the water.

STEP 2: Then counter twist the end of the hose before sticking it in the quick connect with cap and chain on the top of the Fat Sac so it twists back and holds itself in the groove.

STEP 3: Plug the Supa Tsunami Pump into the cigarette lighter accessory plug.

NOTE: To empty do the same thing except the end of the hose goes over the side of the boat first and pump goes on the quick connect with cap and chain on top of the Fat Sac. Then push the pump down into the Sac to prime the Pump.

INSTRUCTIONS FOR THE NEW FAT SAC JUICED EDITION SUPA TSUNAMI QUICK CONNECT PUMP SYSTEM

The new juiced Supa Tsunami Pump is the fastest, most compact and lightweight pump that you put over the side of the boat and plug into the cigarette lighter accessory plug to manually fill and empty the Fat Sacs. It is made to go on and off the Fat Sacs very fast and easy to save time. The new tiger hose on the Supa Tsunami Pump (W709-SUPA) allows you to clearly see when the water is flowing good. It also allows you to see if there are any air bubbles, weeds, sand or dirt in it that are slowing the flow or are being pumped into your Fat Sac.

NOTE: USE MORE THAN ONE SUPA TSUNAMI PUMP TO SAVE TIME FILLING AND EMPTYING ONE OR MULTIPLE SACS.

WARNING:

Do not fill Sacs unattended.

Do not exceed weight limits for boat capabilities.

No sharp turns when using Sacs.

No fast starts and stops with using Sacs.

Do not be under the influence of drugs and/or alcohol when using Fat Sacs period.



3879 North Richards Street ■ Milwaukee, WI 53212 ■ PHONE 414-964-3668 ■ FAX 414-964-5767

E-MAIL orders@fatsac.com or orders@barefootinternational.com ■ WEB www.fatsac.com ■ [@FatSacWake](https://www.instagram.com/FatSacWake)