

MODEL

Naos+ 55"	TT-5521IP
Naos+ 65"	TT-6521IP
Naos+ 75"	TT-7521IP
Naos+ 86"	TT-8621IP

PANEL

Backlight	Direct LED (Wide color gamut + Anti blue light)
Glass Surface	Anti-Glare+Anti-Fingerprint, + Antimicrobial Tempered Glass
Bonding Technology	Certified Optical Bonding
Display Area	55": 1211 x 682 mm
	65": 1428 x 804 mm
	75": 1650 x 928 mm
	86": 1895 x 1066 mm
Display Ratio	16:09
Resolution	3840 x 2160 (4K)
Colours	1,07 Billion
Brightness	400 cd/m ²
Contrast Ratio (Dynamic)	5000:1
Transparency	>88%
Haze	2%-5%
Touch Surface Hardness	8H

POWER CONSUMPTION

Standard mode	55": 122 W
	65": 128 W
	75": 198 W
	86": 234 W
Standby mode	<0,5 W

TOUCH

Touch Technology	Projected Capacitive Touch (PCAP)
Touch Points	20 Windows
Touch Screen Writing Tools	Passive pen, Finger, Fist
Number of stylus	2 x PCAP Passive Pen (No battery)
Accuracy	±1 mm
HID Support	Yes

SPEAKER

Speaker Position	Downward
Speaker Rated Impedance	55": 6 Ω
	65": 8 Ω
	75": 8 Ω
	86": 8 Ω
Speaker Max.Power Output	55": 20 W x 2
	65": 15 W x 2
	75": 15 W x 2
	86": 15 W x 2

I/O

HDMI In (4K60 Hz)	3 (HDMI 1 w/ARC)
HDMI Out (4K60 Hz)	1
USB Type B (Touch)	3
USB 3.0 Type C (Powered 65 W)	1
USB 2.0 (Embedded)	1
USB 3.0 (Dynamic)	2
Gigabit LAN (RJ45)	1 (Built-in HUB for OPS/SDM Pass through)
RS-232	1
Mic In	1
Line Out	1
SPDIF Out	1
OPS Connector	1
SDM-S Slot	1
Power Out Connect (180 W)	1

SMART SYSTEM

SoC Chipset	MSD3683QTA
RAM	3 GB (DDR3)
Storage	64 GB
Operating System	On screen display (Basic Settings)
Formats Support For Image	JPEG, BMP, PNG
Formats Support For Video	MPEG2, MPEG4, H264
Formats Support For Audio	WMA, MP3, M4A, (AAC)

EXTRA FIRMWARE FEATURES

CEC	✓
-----	---

TRANSPORTATION / STORAGE

Outline Dimensions (Excl. wall mount)	55": 1289,9 x 764,1 x 72,6 mm
	65": 1509,1 x 886,2 x 83,1 mm
	75": 1731,1 x 1010 x 86,3 mm
	86": 1977 x 1149,9 x 86,3 mm
Net Weight	55": 26 Kg
	65": 36 Kg
	75": 49 Kg
	86": 59 Kg
VESA	55": 400 x 400 mm
	65": 600 x 400 mm
	75": 800 x 400 mm
	86": 800 x 400 mm