

OSRAM CFL SQUARE 4 pins



- Low-profile wall and ceiling luminaires
- Public buildings, reception areas, offices, corridors, etc.
- Shops
- Supermarkets and department stores
- · Hotels, restaurants

Product benefits

- Square shape provides uniform distribution of light
- · No shadows at either end and no dark patches
- Very economical
- · Extremely low profile
- Good quality of light
- · Long service life

Product features

- Short and compact pin-base lamp with double-turn tubes
- · Single-ended four-pin plug-in GR10q base
- · Average life: up to 10,000 h
- Color rendering index Ra: 80...89





Technical data

Product description	Nominal wattage	Rated lamp efficacy (standard condition)	Rated color rendering index Ra	Rated color temperature	Luminous flux at 25 °C	Base (standard designation)
16 W/827 GR10Q	16 W	66 lm/W	8089	2700 K	1050 lm	GR10q
28 W/827 GR10Q	28 W	73 lm/W	8089	2700 K	2050 lm	GR10q
28 W/835 GR10Q	28 W	73 lm/W	8089	3500 K	2050 lm	GR10q
38 W/827 GR10Q	38 W	71 lm/W	8089	2700 K	2700 lm	GR10q
38 W/835 GR10Q	38 W	71 lm/W	8089	3500 K	2700 lm	GR10q
16 W/835 GR10Q	16 W	66 lm/W	8089	3500 K	1050 lm	GR10q

Product description	Base (standard designation)	Light color	Lifespan	EEI – Energy Label
16 W/827 GR10Q	GR10q	827	10000 h	В
28 W/827 GR10Q	GR10q	827	10000 h	В
28 W/835 GR10Q	GR10q	835	10000 h	В
38 W/827 GR10Q	GR10q	827	10000 h	В
38 W/835 GR10Q	GR10q	835	10000 h	В
16 W/835 GR10Q	GR10q	835	10000 h	В

Product family datasheet



	_		•
FOILE	nmant	/ Acces	CALIDC
Luui	DILLETT	/ MLLES	3UI IE3

• Suitable for operation on electronic and conventional control gear

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp

Application advice

For more detailed application information and graphics please see product datasheet.

Product family datasheet



	is			

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.