

GRAS 43AC-S1

CCP Ear Simulator Kit
According to IEC 60318-4



Connection: 0 V/CCP
Volume: 1260 @ 500 Hz
Dyn range: 25 dB(A) to 150 dB
ANSI: S3.7
IEC: 60318-4

The GRAS 43AC-S1 CCP Ear Simulator Kit according to IEC 60318-4 is a complete test-jig for acoustical measurements on earphones coupled to the ear by inserts such as tubes and ear moulds.

The GRAS 43AC-S1 is a complete test jig for acoustically testing earphones coupled to the ear via inserts such as tubes and ear moulds and complies with the following international requirements:

- IEC 60318-4: Occluded-ear simulator for the measurement of earphones coupled to the ear by ear inserts.

The 43AC-S1 comprises:

- [GRAS RA0045-S1](#) Ear Simulator
- [GRAS 40AO](#) 1/2" Prepolarized Pressure Microphone
- [GRAS 26CB](#) 1/4" CCP Standard Preamplifier with Microdot Connector
- [GRAS RA0001](#) Right-angled Adapter
- [GRAS RA0052](#) Test Jig
- GRAS AA0070 3m Microdot-BNC Cable

The Test Jig has an adjustable spring-loaded arm to exert a variable force on the test object.

Click [GRAS RA0045-S1](#) for more information about the RA0045-S1 Ear Simulator.

An externally polarized version is available, [GRAS 43AC](#).

Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	25
Theoretical dynamic range upper limit with GRAS CCP preamplifier	dB	150
Set sensitivity @ 250 Hz (± 2 dB)	mV/Pa	12
Set sensitivity @ 250 Hz (± 2 dB)	dB re 1V/Pa	-38.5
Coupler volume	mm ³	1260 @ 500 Hz
Resonance frequency	kHz	13.5
Temperature range, operation	°C / °F	- 30 to 60 / -22 to 140
Temperature coefficient @250 Hz	dB/°C / dB/°F	- 0.01 / -0.006
Humidity range non condensing	% RH	0 to 75
ANSI standard		S3.7
IEC standard		60318-4 (former 60711)
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Connector type		Microdot 10/32
Weight	g / oz	1.55 / 54.675

Optional Items

[GRAS RA0196](#)

High-tension springs (set of two)

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK
GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.gras.dk
gras@gras.dk

USA
GRAS SOUND & VIBRATION
5750 S.W. Arctic Drive
Beaverton, OR 97005
Tel: 503-627-0832
Toll Free: 800-231-7350
www.gras.us
sales@gras.us

CHINA
GRAS SOUND & VIBRATION
Room 303, Building T6
Hongqiaohui, 990, Shenchang Road
Minhang District, Shanghai
China, 201106
Tel: +86 21 64203370
www.gras.com.cn
cnsales@gras.dk



ABOUT GRAS SOUND & VIBRATION

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

GRAS Sound
& Vibration