



Ethernet to 8-Port RS-422, RS-485 Serial Server

Part: 4802-TB8 | **Model:** SeaLINK+8.422 Kit

The 4802-TB8 kit includes eight TB34 terminal blocks that simplify RS-422 and RS-485 field wiring. Each terminal block adapter includes a DB9 female connector and five screw terminals.

The SeaLINK 4802 Ethernet to serial server is the easiest way to connect RS-422 or RS-485 serial devices to your Ethernet network. SeaLINK® products use industry-standard RFC 2217 TCP/IP protocol for maximizing compatibility with the widest range of applications and devices.

Sealevel's SeaLINK software drivers and utilities make installation and operation easy using Microsoft Windows operating systems. After software installation, the 4802's serial ports appear as virtual COM ports to the host machine. Standard serial operating calls are transparently redirected to the 4802, guaranteeing compatibility with legacy serial devices and enabling backward compatibility with existing software. Serial tunneling is also supported, allowing two native serial devices to communicate over a network. Alternatively, raw data socket mode is supported, eliminating the need for a driver.

To simplify installation and configuration, a printed copy of the SeaLINK QuickStart Guide is included with all Ethernet serial server orders.

Features & Specifications

Ethernet to 8-Port RS-422, RS-485 Serial Server Kit

Part: 4802-TB8 | **Model:** SeaLINK+8.422 Kit

Features

- Ethernet 10/100BaseT (autosense)
- Each port individually configurable for RS-422 or RS-485
- Automatic RS-485 enable/disable
- Appears as a virtual COM port to host machine
- Data rates to 230.4K bps
- Supports custom baud rates and 9-bit protocol
- Hot-swappable
- Built-in watchdog/reset circuit for fault tolerance
- Eight DB9M connectors
- DIN rail mounting option (Item # DR103)
- Includes 120V AC adapter that outputs 5VDC @ 2.4A (Item# TR101)
- Includes 7' Ethernet patch cable (Item# CA246) and 7' Ethernet crossover cable (Item# CA251)
- Sealevel SeaLINK software supports Microsoft Windows and Linux operating systems
- Kit includes eight TB34 terminal block adapters

Specifications

Family	SeaLINK
Dimensions	8.6 (L) x 6.1 (W) x 2.0 (H)
Electrical Interface	RS-422, RS-485
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	Ethernet
Max Data Distance	4000 feet
Max Data Rate	230.4K bps
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	8
Power Requirement	+5V @ 1A
Serial Connectors	DB9M
Storage Temperature	-50°C to 105°C (-58°F to 221°F)