

# DESKTOP COLOR LABEL PRINTERS

BRILLIANT, FULL-COLOR PRODUCT LABELS ON-DEMAND

**PRIMERA**  
TECHNOLOGY, INC.

**NEW**



## **LX600** COLOR LABEL PRINTER

LX600 encompasses all the same quality features as the LX610 without the built-in die-cutting. It's perfect for a range of industries including health and beauty, food and beverage, chemicals and more.

### **LX600 Features Include:**

- » Color inkjet printing at up to 4800 dpi
- » Print width of 0.5" to 5"
- » Interchangeable pigment and dye inks
- » One high yield tri-color ink cartridge
- » Pizza-wheel style label cutter

|                               |  |
|-------------------------------|--|
| <b>Print Method:</b>          | Thermal inkjet; Dye & Pigment ink  |
| <b>Print Resolution:</b>      | Up to 1200 x 4800 dpi  |
| <b>Print/Cut Speeds:</b>      | Print Speeds: 4.5" per second  |
| <b>Print Head:</b>            | New print head with every cartridge change   |
| <b>Ink:</b>                   | Single high capacity Cyan, Magenta, Yellow ink cartridge, process black  |
| <b>Colors:</b>                | 16.7 million   |
| <b>Color Matching:</b>        | ICC color profiles for all Primera-supplied media. Ability to add custom ICC color profiles for other media types.   |
| <b>Print Width:</b>           | 0.5" (13mm) to 5" (127mm)  |
| <b>Media Width:</b>           | 2.125" (54mm) to 5.25" (133mm)   |
| <b>Media Types:</b>           | Roll-fed pressure-sensitive labels, roll-fed tags, fan-fold labels or tag  |
| <b>Media Sensing:</b>         | Moveable see-through sensor for die-cut labels; reflective sensor for labels and tags with black stripe; can use continuous and pre-printed labels and tags. |
| <b>Supply Roll:</b>           | 6" (152mm) maximum diameter on 3" (76mm) core.   |
| <b>Ink Level Warning:</b>     | Calculates actual number of prints remaining based upon ink usage of graphics being printed (patent-pending)   |
| <b>Indicator Lights:</b>      | Power, Ink   |
| <b>Controls:</b>              | Pause, Feed, Unload  |
| <b>Operating Systems:</b>     | Windows® 7/8x/10+  |
| <b>Data Interface:</b>        | USB 2.0  |
| <b>Label Design Software:</b> | Seagull Scientific Bartender® UltraLite Software version included; can also be used with most other popular label design & graphics programs.                |
| <b>Electrical Rating:</b>     | 12VDC, 5.0A  |
| <b>Power Requirements:</b>    | 100-240VAC, 50/60 Hz, 60 watts   |
| <b>Certifications:</b>        | UL, UL-C, CE, FCC Class A  |
| <b>California Prop 65:</b>    | <b>⚠️ WARNING:</b> Cancer and Reproductive Toxin - <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>  |
| <b>Weight:</b>                | 11.5 lbs. (5.2 kg)   |
| <b>Dimensions:</b>            | 13.6"W x 9.5"H x 17"D<br>(345mmW x 242mmH x 432mmD)  |
| <b>Included:</b>              | Bartender UltraLit software for Windows & an ultra-high yield CMY dye ink cartridge.   |



1(800)268-7636  
(780)434-9152  
NeumannMarking.com  
Shop.NeumannMarking.com