KÄRCHER

KARCHER

^{KX}RCHER

ROBUST COMMERCIAL-DUTY FLOOR CLEANING MACHINES.

Engineered for rugged dependability and rigorous demands.

Engineered for rugged dependability.

Kärcher's line of commercial-duty floor machines are built utilizing cast aluminum housings rather than poly or stamped frames to endure the rigorous demands of commercial cleaning with rugged construction and durable time-tested components.



1 Performance

- New startup capacitor and run capacitor are more robust for greater efficiency operation
- Single motor with new die cast aluminum housing for smoother operation and better protection of the machine

2 Convenient

- New, stronger handle housing for smoother operation and longer life
- Fully adjustable handle height system for ease of use
- Large non-marking wheels for hygiene, easy transport and protection.

3 Safety

- New cord strain relief system minimizes cord breaks, kinks and tears
- Mechanical safety interlock prevents accidental start-ups
- Built-in circuit breaker protects the motor
- All models come equipped with high mounted handle lock / height adjustment, non-marking PVC bumper, dual main switch levers, and thumb activated safety interlock

Technical data and equipment.



Strong, solid and robust operation.

The BDS 43/175 C , BDS 51/175 C floor machines are high quality, durable units that offer power and versatility for scrubbing and stripping. They feature an adjustable handle to accommodate various user heights and five inch non-marking wheels to allow easy transportation.

Floor Machine Built for Durability and Reliability

- Robust motor for everyday reliability
- Separate start and run capacitors for durability
- Cord strain relief to keep cord from breaking or tearing
- Strong and solid handle housing for trouble free operation

BDS 43/175 C BDS 51/175 C

| TECHNICAL SPECIFICATIONS | | | |
|------------------------------------|----------|----------------|-----------------|
| Pad size | in | 17 | 20 |
| Pad speed | rpm | 175 | 175 |
| Theoretical/practical productivity | sq.ft/hr | 1,923 | 2,222 |
| Operating noise level | dBA | 63 | 63 |
| Voltage | V | 115 | 115 |
| Motor | hp | 1.5 | 1.5 |
| Wheel diameter | in | 5 x 1.25 | 5 x 1.25 |
| Power cord length | ft | 50 | 50 |
| Weight w/ Cord | lbs | 91 | 94 |
| Dimensions (L x W x H) | in | 23 x 16.5 x 46 | 24.5 x 19.5x 46 |

EQUIPMENT

| Order No. | Description |
|-------------|------------------------------|
| 1.009-102.0 | BDS 43/175 C, seventeen-inch |
| 1.009-103.0 | BDS 51/175 C, twenty-inch |

ACCESSORIES

| AC | CESSORIES | |
|----|-------------|---|
| | Order No. | Description |
| - | 8.600-012.0 | Pad driver, 17-inch with clutch plate (BDS 43/175) |
| - | 8.628-430.0 | Pad driver, 20-inch with clutch plate (BDS 51/175) |
| - | 8.628-429.0 | Pad driver, 20-inch for dual speed machine (BDS 51/175-300) |
| | 8.645-238.0 | Solution tank 4 gallon |
| | 8.600-507.0 | Center lock |
| | 8.628-371.0 | 17-inch aggressive grit brush with clutch plate |
| | 8.600-013.0 | 17-inch mild grit brush with clutch plate |
| | 8.600-014.0 | 17-inch nylon polish brush with clutch plate |
| | 8.628-380.0 | 17-inch nylon scrub brush with clutch plate |
| | 8.600-011.0 | 17-inch polypropylene brush with clutch plate |
| | 8.625-258.0 | 17-inch sanding disc |
| | 8.628-369.0 | 20-inch aggressive grit brush with clutch plate |
| | 8.628-378.0 | 20-inch mild grit brush with clutch plate |
| | 8.628-379.0 | 20-inch nylon polish brush with clutch plate |
| | 8.628-377.0 | 20-inch nylon scrub brush with clutch plate |
| | 8.628-370.0 | 20-inch polypropylene brush with clutch plate |
| | 8.625-259.0 | 20-inch sanding disc |

■ Included □ Optional