

CAW Aluminum Series

Dealer Cold Water Pressure Washers







This electric series can be used to clean in various locations. Mount it in a garage, shop or wash bay to blast away mud and dirt from vehicles and equipment.

PUMP

- Factory preset stainless-steel and brass trapping unloader
- Forged brass manifold
- Thermal relief valve
- External quick connect low pressure detergent injector
- Pump accepts incoming water up to 165°F (175°F on CAW-4004-0ME1)

MOTOR

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 4-foot power cord

FRAME

· Aluminum frame with wall-mounting brackets

COMPONENTS

- · Time delay shutdown
- Remote mounted electrical box, must be within 3½-feet of unit

UNIT INCLUDES

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x %-inch non-marking high pressure hose
- · Professional-grade insulated trigger gun with safety lock-off
- 36-inch adjustable pressure insulated dual lance (48-inch on CAW-4004-0ME1)

LIMITED WARRANTY

• 1 year electric motor



CAW Aluminum Series

Cold Water - Electric - Wall-Mount - Direct Drive

PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	DIMENSIONS (LxWxH)*	SHIP WT.	NET WT.
2000	3.9	6.0 HP, 230V, 1Ø, 24.1A	General	NEMA 6-30P	34x17.25x18in.	248 lb.	188 lb.
2000	3.9	6.0 HP, 230V, 3Ø, 17.3A	General	NEMA L15-20P	34x17.25x18in.	223 lb.	163 lb.
3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	General	NEMA 6-50P	34x17.25x18in.	268 lb.	208 lb.
3000	3.9	8.0 HP, 230V, 3Ø, 22.8A	General	NEMA L15-30P	34x17.25x18in.	253 lb.	193 lb.
4000	4.0	10.0 HP, 230V, 1Ø, 40.8A	General	NEMA 6-50P	34x18x19in.	368 lb.	293 lb.
	2000 2000 3000 3000	2000 3.9 2000 3.9 3000 3.9 3000 3.9	2000 3.9 6.0 HP, 230V, 1Ø, 24.1A 2000 3.9 6.0 HP, 230V, 3Ø, 17.3A 3000 3.9 8.0 HP, 230V, 1Ø, 34.5A 3000 3.9 8.0 HP, 230V, 3Ø, 22.8A	2000 3.9 6.0 HP, 230V, 1Ø, 24.1A General 2000 3.9 6.0 HP, 230V, 3Ø, 17.3A General 3000 3.9 8.0 HP, 230V, 1Ø, 34.5A General 3000 3.9 8.0 HP, 230V, 3Ø, 22.8A General	2000 3.9 6.0 HP, 230V, 1Ø, 24.1A General NEMA 6-30P 2000 3.9 6.0 HP, 230V, 3Ø, 17.3A General NEMA L15-20P 3000 3.9 8.0 HP, 230V, 1Ø, 34.5A General NEMA 6-50P 3000 3.9 8.0 HP, 230V, 3Ø, 22.8A General NEMA L15-30P	2000 3.9 6.0 HP, 230V, 10, 24.1A General NEMA 6-30P 34x17.25x18in. 2000 3.9 6.0 HP, 230V, 30, 17.3A General NEMA L15-20P 34x17.25x18in. 3000 3.9 8.0 HP, 230V, 10, 34.5A General NEMA 6-50P 34x17.25x18in. 3000 3.9 8.0 HP, 230V, 30, 22.8A General NEMA L15-30P 34x17.25x18in.	2000 3.9 6.0 HP, 230V, 10, 24.1A General NEMA 6-30P 34x17.25x18in. 248 lb. 2000 3.9 6.0 HP, 230V, 30, 17.3A General NEMA L15-20P 34x17.25x18in. 223 lb. 3000 3.9 8.0 HP, 230V, 10, 34.5A General NEMA 6-50P 34x17.25x18in. 268 lb. 3000 3.9 8.0 HP, 230V, 30, 22.8A General NEMA L15-30P 34x17.25x18in. 253 lb.

*Dimensions do not include the mounting brackets.

ACCESSORY:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x %-inch non-marking hose – For when you need extra hose for added mobility	All models

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0078	Remote box – Adds control box, may be mounted away from unit to control on/off	All models
CX-0109	Additional remotes, up to 3 qty. – Additional remotes that may be added to unit after the first remote is installed; requires remote box option CX-0078	All models
CX-0110	460V on 6.0-HP, 3Ø model – When 460V of power is available	CAW-2004-0ME3
CX-0111	460V on 8.0-HP, 3Ø model – When 460V of power is available	CAW-3004-0ME3
CX-0112	Auto start/stop – When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart	All models



NEMA L15-20P, 20-amp plug



NEMA L15-30P, 30-amp plug



NEMA 6-30P, 30-amp plug



NEMA 6-50P, 50-amp plug

