



HHB Series — Belt Drive



HHB-2503-0E2A

Tackle tough grease, grime and stubborn stains with the portable HHB Series. This series features an open drip-proof motor and stainless-steel coil wrap heat exchanger.

PUMP

- Adjustable high pressure detergent injector
- Factory preset unloader

MOTOR

- Open drip-proof electric motor with manual thermal overload protection
- 35-foot power cord

FRAME

- Powder coated steel frame assembly
- 13-inch flat-free tires

COMPONENTS

- Stainless-steel coil wrap with horizontal schedule 80 pip coil
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Racor fuel filter/water separator
- Adjustable thermostat
- Polyethylene float tank with inlet filter screen
- 10-gallon polyethylene fuel tank

MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25°, 40° and low pressure nozzle (except on HHB-303-0E1A)
- 50-foot x 3/8-inch high pressure hose (50-foot steam hose on HHB-303-0E1A)
- Adjustable pressure insulated dual lance (except on HHB-303-0E1A)
- Single lance with dual insulated grips; steam nozzle (HHB-303-0E1A)
- Professional-grade insulated trigger gun with safety lock-off

LIMITED WARRANTY

- 1 year electric motor

CERTIFICATION

- CSA Certified – US and Canada



Portable Electric

Hot Water – HHB Series – Belt Drive

| MODEL NUMBER | PSI | GPM | HORSEPOWER/MOTOR | PUMP | PLUG TYPE | BURNER FUEL TANK CAPACITY | BURNER FUEL CONSUMPTION | BTU PER HOUR | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|---------------------------|------|-----|-------------------------|------|------------|---------------------------|-------------------------|--------------|--------------------|----------|---------|
| HHB-1002-0E1A | 1000 | 2.0 | 1.5 HP, 115V, 1Ø, 16.2A | AR | NEMA 5-20P | 10.0 gallons | 1.23 gph | 172,200 | 57x30x41.5in. | 606 lb. | 486 lb. |
| HHB-1003-0E1A | 1000 | 2.8 | 2.0 HP, 115V, 1Ø, 20.0A | AR | NEMA 5-20P | 10.0 gallons | 1.84 gph | 257,600 | 57x30x41.5in. | 610 lb. | 490 lb. |
| HHB-1502-0E1A | 1500 | 1.8 | 2.0 HP, 115V, 1Ø, 19.9A | AR | NEMA 5-20P | 10.0 gallons | 1.23 gph | 172,200 | 57x30x41.5in. | 610 lb. | 490 lb. |
| HHB-2503-0E2A | 2500 | 2.8 | 6.0 HP, 230V, 1Ø, 28.0A | AR | NEMA 6-30P | 10.0 gallons | 1.84 gph | 257,600 | 57x30x41.5in. | 650 lb. | 540 lb. |
| HHB-303-0E1A [^] | 300 | 2.5 | 1.5 HP, 115V, 1Ø, 12.5A | AR | NEMA 5-15P | 10.0 gallons | 2.76 gph | 386,400 | 57x30x41.5in. | 480 lb. | 460 lb. |

[^]Steam unit.



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



NEMA 6-30P,
30-amp plug



HHB-2503-0E2A

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.