

# HSS & HSDS

## SUPERSKID SERIES



PRESSURE WASHERS / SINCE 1970

### FEATURES

- 5.0 to 9.5 GPM @ 2500 to 3500 PSI
- Stainless Steel
- Coil Wrap
- Electric Start



HOT WATER

DIESEL

BELT DRIVE

High efficiency **Wayne 12VDC Burner** with proprietary controller

**Ready plumbed** for connection to remote water tank

50-ft. of two-wire, heavy-duty abrasion resistant **hose**

**High flow VRT100** unloader handles 27 GPM @ 5075 PSI

**Heavy-duty trigger gun and wand** with insulated cool grips

**Water resistant control panel** includes adjustable temperature control, heavy-duty heater switch, hour meter, volt meter, keyed ignition switch, and nozzle storage

**Hotsy triplex, tri-banded belt drive,** positive-displacement pump carries a 7-year warranty

Optional adjustable **high-pressure detergent kit** (included with the float tank kit)

HSDS models offer super duty **Hawk pump** with lower pump RPMs for long lasting durability

**Optional steam combination control**

**Upright, diesel-fired burner** with stainless-steel coil skin is highly efficient and maintains constant hot water using diesel fuel

**Removable frame supports** for easy service access

**3/4-inch schedule 80 heating coil** is wrapped with a thick foil backed blanket insulation, carrying a 5-year non prorated warranty

**Rugged square tube frame** protects machine's vital components

**Fuel/water separator** prolongs fuel pump life

**Tier IV Kubota Diesel engine** in 16 or 24 HP operate longer with two diesel crossedlinked HDPE tanks, 25 gallons each

**Safety relief valve** protects machine and user

**Optional large float tank** maintains constant pressure and flow while preventing sediment from entering the machine's components



### OPTIONS FOR HSS/HSDS SERIES

**Dual Gun Kit** - includes necessary fittings, extra hose gun and wand

**Steam Kit** - includes necessary fittings and panel mount control valve

**Float Tank Kit** - includes float tank, necessary fittings and panel mount detergent metering valve



#### Pump size comparison:

The HFR and HHP pumps from Leuco used in the Super Duty models dwarf the standard HX.

THE **BRAND** THE PROS USE



## SUPER SKID HSS SERIES

Hot-Water DIESEL Belt Drive Models

## POWERFUL MODELS FOR TOUGH INDUSTRIAL CLEANING.

■ Gas/Diesel-Powered ■ 4.5 to 8.0 GPM @ 3000 to 4000 PSI ■ Electric Start

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS (LXWXH)	SHIP WT (Lbs)
HSS-503069E	1.110-604.0	5.0	3000	Kubota Z602-E4B	599	12V DC	465,000	HX5843R.2	50'-3/8"	73"x37"x64"	1305
HSS-653569E	1.110-605.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	565,000	HX8043R.2	50'-3/8"	73"x37"x64"	1710
HSS-803069E	1.110-606.0	8.0	3000	Kubota D1105-E4B	1123	12V DC	635,000	HX9536.2	50'-1/2"	73"x37"x64"	1715
HSS-952569E	1.110-607.0	9.5	2500	Kubota D1105-E4B	1123	12V DC	780,000	HX1036R.2	50'-1/2"	73"x37"x64"	1715

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS (LXWXH)	SHIP WT (Lbs)
HSDS-503069E	1.110-616.0	5.0	3000	Kubota Z602-E4B	599	12V DC	465,000	HHP2750R	50'-3/8"	73"x37"x64"	1610
HSDS-653569E	1.110-617.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	565,000	HHP3650R	50'-3/8"	73"x37"x64"	2005
HSDS-803069E	1.110-618.0	8.0	3000	Kubota D1105-E4B	1123	12V DC	635,000	HFR40FR	50'-1/2"	73"x37"x64"	2015
HSDS-952569E	1.110-619.0	9.5	2500	Kubota D1105-E4B	1123	12V DC	780,000	HFR60FR	50'-1/2"	73"x37"x64"	2020


All models are Electric Start. 12V battery required for all models, but not supplied

### DETERGENTS



To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

### PARTS & ACCESSORIES



Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

### SERVICE



Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tune-ups. Plus, we repair all brands.

**NOTE:** We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +\_10% and in some cases are tighter within +\_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2021 Kärcher North America  
P/N HOT\_HSS Effective 06/21

Distributed by:



NorthBayEquipment.com | 707.585.0100  
Serving the counties of Lake, Marin, Mendocino, Napa, Solano, and Sonoma.



PacificBayEquipment.com | 800.640.1227  
Serving the counties of Alameda, Contra Costa, Calaveras, Merced, San Francisco, San Joaquin, Stanislaus, & Tuolumne.

Premier provider of innovative cleaning, sanitizing, disinfecting & water treatment solutions since 1976.