


# KÄRCHER

makes a difference



## MAXIMUM MANEUVERABILITY.


A ride-on sweeper boasting intuitive operation in a compact and agile package.

# KM 85/50 R BP



## Compact, agile and intuitive.

The KM 85/50 R Bp is a battery-powered ride-on sweeper perfect for congested areas. Its compact design and high maneuverability make cleaning faster than ever in confined spaces, narrow corridors and around sharp corners. The KM 85/50 R Bp is extremely easy to operate and maintain, and boasts impressive area performance outdoors, making it a versatile and efficient entry-level choice for ride-on sweepers.



### 1 Clever container concept

- 2 tanks with handle grips and transport wheels for easy disposal
- Smooth edges around waste container prevents residue

### 2 Efficient filter system

- Polyester flat pleated filter
- Effective cleaning with dual scraper

### 3 Ergonomic design for enhanced performance and comfort

- Clear and simple operation of all components, no training required
- Easy, tool-free seat adjustment for operator comfort
- Adjustable rotation speed depending on type and amount of dirt, reducing dust turbulence
- Drives through door openings as narrow as 36" and maneuvers turns in aisles as narrow as 78"

### 4 Integrated home base system and storage areas

- Versatile and practical storage area for other cleaning utensils such as brushes and cloths

# Technical data and equipment.

## KM 85/50 R BP

### TECHNICAL SPECIFICATIONS

|   |                     |                 |
|---|---------------------|-----------------|
| Working width (main broom)                | in                  | 24.2            |
| Working width (1/2 side brooms)           | in                  | 33.5 / 41.3     |
| Debris container capacity                 | gal                 | 13.2 ( 2 x 6.6) |
| Max. working speed                        | mph                 | 3.7             |
| Theoretical/Practical productivity (1 SB) | ft <sup>2</sup> /hr | 54,900 / 32,940 |
| Theoretical/Practical productivity (2 SB) | ft <sup>2</sup> /hr | 67,815 / 40,685 |
| Operating noise level                     | dBA                 | 69              |
| Minimum turning radius                    | ft                  | 3.3             |
| Climbing ability (max. slope)             |                     | 12%             |
| Weight (with batteries)                   | lbs                 | 555             |
| Dimensions (L x W x H)                    | in                  | 50 x 35 x 46    |

### EQUIPMENT

| Order No.   | Item Description                |
|-------------|---------------------------------|
| 9.841-453.0 | KM 85/50 R Bp Wet, 1 side broom |
| 9.841-454.0 | KM 85/50 R Bp AGM, 1 side broom |

### ACCESSORIES

| Order No.     | Description                    | Image |
|---------------|--------------------------------|-------|
| ■ 4.762-430.0 | Main brush, standard           |       |
| ■ 6.906-132.0 | 1-side brush, standard         | 1     |
| ■ 2.852-502.0 | Pneumatic tire (1 each)        | 2     |
| ■ 5.731-585.0 | Flat pleated filter            | 3     |
| □ 6.435-431.0 | Solid rubber non-marking wheel |       |
| □ 4.762-442.0 | Main brush, soft               | 4     |
| □ 4.762-443.0 | Main brush, hard               | 5     |
| □ 4.762-441.0 | Main brush, antistatic         | 6     |
| □ 6.905-626.0 | Side brush, soft               | 7     |
| □ 6.905-625.0 | Side brush, hard               | 7     |
| □ 2.852-499.0 | Carpet cleaning kit            |       |
| □ 2.852-321.0 | Additional left side brush kit |       |
| □ 2.852-500.0 | Warning beacon                 | 8     |
| □ 5.035-488.0 | Home base adapter              | 9     |
| □ 6.980-077.0 | Home base hook                 | 10    |

■ Included □ Optional

